

Carbură
monobloc

Tip
N

e8
4

Z
4

$a_g=0,3xD$

DIN
6535-HB

HPC

TPC



Execuție:

20 3025 – Cu coadă detalonată (Dimensiunile L_4 și D_4).



$v_c = \text{m/min}$	Alu Termo Pl.	Alu	Aliaj Alu >10% Si						TOOLOX® 33 HRC	TOOLOX® 44 HRC	HARDOX® 500 <1600 N	INOX <900 N	INOX >900 N	Ti >850 N	Fontă + FGS	CuZn	Grafit GRP CRP	Uni				Aer	
Cod ISO:	N	N	N	P	P	P	P	P	H	H	H	M	M	S	K	N	N						
20 3018 –				210	195	170	150	145	95	70		85	75	50				○		●	○	●	
20 3022 –				100	90	80	70	65	55	50		45	40	30				○		●	○	●	
20 3025 –				120	110	100	90	80	70	60		55	45	35				○		●	○	●	

Ref. = \varnothing e8 D_c	20 3018 20 3022 20 3025			20 3018			20 3022		20 3025		h_6		INOX >900 N f_z
	HPC / TPC	HPC foarte lungă	HPC foarte lungă	20 3018	20 3022	20 3025	20 3025	20 3025	20 3018	20 3022 20 3025			
mm	TiAIN	TiAIN	TiAIN	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
6	XXX	—	XXX	32	—	12	42	5,5	80	100	6	0,4	0,040
8	XXX	—	XXX	32	—	16	62	7,4	90	100	8	0,4	0,040
10	XXX	—	XXX	38	—	20	60	9,2	100	100	10	0,5	0,065
12	XXX	XXX	XXX	51	76	24	73	11	100	125	12	0,5	0,065
16	XXX	XXX	XXX	57	76	32	100	15	125	150	16	0,5	0,080
20	XXX	XXX	XXX	57	102	40	98	19	125	175	20	0,5	0,100