


PA 400 AOL

Complete swage fitting for HD 400

(EN 856 4SP), O-ring, metric
female 24° cone, light series
(DKOL), DIN 3865,
material: steel, zincd,
yellow passivated
Article category 1202



Designation	DN	size	inch	thread	tube-Ø	SW	O-ring	T
-------------	----	------	------	--------	--------	----	--------	---

PA 410 AOL	10	6	3/8"	18x1,5	12	22	9,5x2	16,05
PA 413 AOL	13	8	1/2"	22x1,5	15	27	12x2	20,05
PA 416 AOL	16	10	5/8"	26x1,5	18	32	15x2	24,05
PA 416 AOL 20	16	10	5/8"	30x2	22	36	20x2	27,40
PA 420 AOL	20	12	3/4"	30x2	22	36	20x2	27,40
PA 425 AOL	25	16	1"	36x2	28	41	25x2	33,40




PA 400 AOL 45

Complete swage fitting 45° for HD 400

(EN 856 4SP), O-ring, metric
female 24° cone, light series
(DKOL), DIN 3865,
material: steel, zincd,
yellow passivated

Article category 1201



Designation

DN

size

inch

thread

tube-Ø

SW

O-ring


T

PA 410 AOL 45	10	6	3/8"	18x1,5	12	22	9x1,5	16,05
PA 413 AOL 45	13	8	1/2"	22x1,5	15	27	12x2	20,05
PA 416 AOL 45	16	10	5/8"	26x1,5	18	32	15x2	24,05
PA 420 AOL 45	19	12	3/4"	30x2	22	36	20x2	27,40
PA 425 AOL 45	25	16	1"	36x2	28	41	26x2	33,40

PA 400 AOL 90

Complete swage fitting 90° for HD 400

(EN 856 4SP), O-ring, metric
female 24° cone, light series
(DKOL), DIN 3865,
material: steel, zинced,
yellow passivated
Article category 1202



Designation

DN

size

inch

thread

tube-Ø

SW

O-ring


T

PA 406 AOL 08 90	6	4	1/4"	16x1,5	10	19	7,5x1,5	14,05
PA 410 AOL 90	10	6	3/8"	18x1,5	12	22	9x1,5	16,05
PA 413 AOL 90	13	8	1/2"	22x1,5	15	27	12x2	20,05
PA 416 AOL 90	16	10	5/8"	26x1,5	18	32	15x2	24,05
PA 420 AOL 90	20	12	3/4"	30x2	22	36	20x2	27,40
PA 425 AOL 90	25	16	1"	36x2	28	41	26x2	33,40

PA 500 AOL

Complete swage fitting for HD 500

(EN 856 4SH) O-ring, metric
female 24° cone, light series
(DKOL), DIN 3865,
material: steel, zincd,
yellow passivated
Article category 1202



Designation

DN

size

inch

thread

tube-Ø

O-ring

T

PA 532 AOL

32

20

1"1/4

M 45x2

35

32x2,5

42,40

PA 540 AOL

40

24

1"1/2

M 52x2

42


38x2,5

49,40

PA 500 AOL 45

Complete swage fitting 45° for HD 500

(EN 865 4SH), O-ring, metric
female 24° cone, light series
(DKOL), DIN 3865,
material: steel, zincd,
yellow passivated
Article category 1202



Designation

DN

size

inch

thread

tube-Ø

O-ring

T


PA 532 AOL 45	32	20	1"1/4	M 45x2	35	32x2,5	42,40
PA 540 AOL 45	40	24	1"1/2	M 52x2	42	38x2,5	49,40

PA 400 A

Complete swage fitting for HD 400

(EN 856 4SP), metric female 60°
cone, DIN 3863 (DKM),
material: steel, zincd,
yellow passivated

Article category 1203



Designation

DN

size

inch

thread

SW

T

PA 420 A

20

12

3/4"

M 30x1,5

36

28,05

PA 425 A

25

16

1"

M 38x1,5

46


36,05

PA 500 A

Complete swage fitting f or HD 500

(EN 856 4SH), metric female 60°
cone, DIN 3863 (DKM),
material: steel, zincd,
yellow passivated

Article category 1203



Designation

DN

size

inch

thread

SW

T


PA 532 A	32	20	1"1/4	M 45x1,5	55	43,05
PA 540 A	40	24	1"1/2	M 52x1,5	60	50,05
PA 550 A	50	32	2"	M 65x2	75	62,40

PA 400 A 45

Complete swage fitting 45° for HD 400

(DIN 856 4SP), metric female 60°
cone, DIN 3863 (DKM),
material: steel, zincd,
yellow passivated

Article category 1203



Designation

DN

size

inch

thread

SW

T


PA 420 A 45	20	12	3/4"	M 30x1,5	36	28,05
PA 425 A 45	25	16	1"	M 38x1,5	46	36,05

PA 500 A 45

Complete swage fitting 45° for HD 500

(EN 856 4SH), metric female 60°
cone, DIN 3863 (DKM),
material: steel, zincd,
yellow passivated

Article category 1203



Designation

DN

size

inch

thread

SW

T


PA 532 A 45	32	20	1"1/4	M 45x1,5	55	43,05
PA 540 A 45	40	24	1"1/2	M 52x1,5	60	50,05
PA 550 A 45	50	32	2"	M 65x2	75	62,40

PA 400 A 90

Complete swage fitting 90° for HD 400

(DIN 856 4SP), metric female 60°
cone, DIN 3863 (DKM),
material: steel, zincd,
yellow passivated

Article category 1203



Designation

DN

size

inch

thread

SW

T

PA 420 A 90

20

12

3/4"

M 30x1,5

36

28,05

PA 425 A 90

25

16

1"

M 38x1,5

46


36,05

PA 500 A 90

Complete swage fitting 90° for HD 500

(EN 856 4SH), metric female 60°
cone, DIN 3863 (DKM),
material: steel, zincd,
yellow passivated

Article category 1203



Designation

DN

size

inch

thread

SW

T


PA 532 A 90	32	20	1"1/4	M 45x1,5	55	43,05
PA 540 A 90	40	24	1"1/2	M 52x1,5	60	50,05
PA 550 A 90	50	32	2"	M 65x2	75	62,40

PA 400 ALI

Complete swage fitting for HD 400

(EN 856 4SP) Japanese series,
JIS metric female 60° cone seat,
JIS 8365 (DK Komatsu),
material: steel, zincd,
yellow passivated

Article category 1203



Designation

DN

size

inch

thread

T

PA 420 ALI

20

12

3/4"


M 30x1,5

28,05

PA 400 FL

Complete swage fitting for HD 400

(EN 856 4SP) metric standpipe,
cutting ring connection, light
series (BEL), DIN 2353,
material: steel, zined,
yellow passivated



Designation

DN

size

inch

tube-Ø

PA 406 FL	6	4	1/4"	8
PA 410 FL	10	6	3/8"	12
PA 413 FL	13	8	1/2"	15
PA 416 FL	16	10	5/8"	18
PA 420 FL	20	12	3/4"	22
PA 425 FL	25	16	1"	28

PA 500 FL

Complete swage fitting for HD 500

(EN 856 4SH) with metric
standpipe, cutting ring
connection, light series (BEL),
DIN 2353,
material: steel, zined,
yellow passivated
Article category 1216



Designation

DN

size

inch

tube-Ø

PA 532 FL

32

20

1"1/4

35

PA 540 FL

40

24

1"1/2


42

PA 400 AFS

Complete swage fitting for HD 400

(EN 856 4SP), metric female
multiseal, heavy series (DKS),
material: steel, zincd,
yellow passivated

Article category 1219



Designation

DN

size

inch

tube-Ø

thread

SW


T

PA 406 AFS	6	4	1/4"	10	M 18x1,5	22	16,05
PA 410 AFS	10	6	3/8"	14	M 22x1,5	27	20,05
PA 416 AFS	16	10	5/8"	20	M 30x2	36	27,40

PA 400 AOS

Complete swage fitting for HD 400

(EN 856 4SP), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zincd, yellow passivated
Article category 1222




Designation	DN	size	inch	thread	tube-Ø	SW	O-ring	T
PA 406 AOS	6	4	1/4"	M 18x1,5	10	22	8x1,5	16,05
PA 406 AOS 04	6	4	1/4"	M 16x1,5	8	19	6x1,5	14,05
PA 410 AOS	10	6	3/8"	M 22x1,5	14	27	12x2	20,05
PA 410 AOS 13	10	6	3/8"	M 24x1,5	16	30	13x2	22,05
PA 410 AOS 08	10	6	3/8"	M 20x1,5	12	24	9x1,5	18,05
PA 413 AOS	12	8	1/2"	M 24x1,5	16	30	13x2	22,05
PA 413 AOS 16	12	8	1/2"	M 30x2	20	36	17,5x2,5	27,40
PA 416 AOS 13	16	10	5/8"	M 24x1,5	16	30	13x2	22,05
PA 416 AOS	16	10	5/8"	M 30x2	20	36	17,5x2,5	27,40
PA 416 AOS 20	16	10	5/8"	M 36x2	25	41	22x2,5	33,40
PA 420 AOS 16	19	12	3/4"	M 30x2	20	36	17,5x2,5	27,40
PA 420 AOS	19	12	3/4"	M 36x2	25	41	22x2,5	33,40
PA 425 AOS	25	16	1"	M 42x2	30	50	27x2,5	39,40
PA 425 AOS 20	25	16	1"	M 36x2	25	41	22x2,5	33,40
PA 425 AOS 32	25	16	1"	M 52x2	38	60	33x2,5	49,40

PA 400 AOS A

Complete interlock swage fitting for HD 400

(EN 856 4SP), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zincd, yellow passivated

Article category 1223



Designation

DN

size

inch

thread

tube

SW

O-ring

T

PA 420 AOS A

20

12

3/4"

M 36x2

25

36

22x2,5


33,40

PA 400 AOS 45

Complete swage fitting 45° for HD 400

(EN 856 4SP), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zined, yellow passivated

Article category 1222



Designation

DN

size

inch

thread

tube-Ø

SW

O-ring

T


PA 406 AOS 04 45	6	4	1/4"	M 14x1,5	8	19	6x1,5	14,05
PA 406 AOS 45	6	4	1/4"	M 18x1,5	10	22	8x1,5	16,05
PA 410 AOS 08 45	10	6	3/8"	M 20x1,5	12	24	9x1,5	18,05
PA 410 AOS 45	10	6	3/8"	M 22x1,5	14	27	12x2	20,05
PA 413 AOS 45	13	8	1/2"	M 24x1,5	16	30	13x2	22,05
PA 416 AOS 45	16	10	5/8"	M 30x2	20	36	17,5x2,5	27,40
PA 420 AOS 45	20	12	3/4"	M 42x2	25	41	22x2,5	39,40
PA 420 AOS 16 45	20	12	3/4"	M 30x2	20	36	17,5x2,5	27,40
PA 425 AOS 32 45	25	16	1"	M 52x2	38	50	33x2,5	49,40
PA 425 AOS 20 45	25	16	1"	M 36x2	25	41	27x2,5	33,40
PA 425 AOS 45	25	16	1"	M 42x2	30	50	27x2,5	39,40

PA 400 AOS 90

Complete swage fitting 90°
for HD 400

(EN 856 4SP), O-ring metric
female 24° cone, heavy series
(DKOS), material: steel, zined,
yellow passivated

Article category 1222



Designation

DN

size

inch

thread

tube-Ø

SW

O-ring

T


PA 406 AOS 04 90	6	4	1/4"	M 14x15	8	19	6x1,5	14,05
PA 406 AOS 90	6	4	1/4"	M 18x1,5	10	22	8x1,5	16,05
PA 410 AOS 08 90	10	6	3/8"	M 20x1,5	12	24	9x1,5	18,05
PA 410 AOS 90	10	6	3/8"	M 22x1,5	14	27	12x2	20,05
PA 413 AOS 90	13	8	1/2"	M 24x1,5	16	30	13x2	22,05
PA 413 AOS 90 L 90	13	8	1/2"	M 24x1,5	16	30	13x2	22,05
PA 413 AOS 90 L 180	13	8	1/2"	M 24x1,5	16	30	13x2	22,05
PA 413 AOS 16 90	13	8	1/2"	M 30x2	20	36	17,5x2,5	27,40
PA 416 AOS 90	16	10	5/8"	M 30x2	20	36	17,5x2,5	27,40
PA 420 AOS 90	20	12	3/4"	M 36x2	25	41	22x2,5	33,40
PA 420 AOS 16 90	20	12	3/4"	M 30x2	20	36	17,5x2,5	27,40
PA 420 AOS 90 L 100	20	12	3/4"	M 36x2	25	41	22x2,5	33,40
PA 420 AOS 25 90	20	12	3/4"	M 42x2	30	50	27x2,5	39,40
PA 425 AOS 90	25	16	1"	M 42x2	30	50	27x2,5	39,40
PA 425 AOS 90 L 100	25	16	1"	M 42x2	30	50	27x2,5	39,40
PA 425 AOS 32 90	25	16	1"	M 52x2	38	60	33x2,5	49,40

PA 500 AOS A

Complete interlock swage fitting for HD 500

(EN 856 4SH), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zincd, yellow passivated

Article category 1222



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>	<i>O-ring</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------	---------------


PA 520 AOS A	20	12	3/4"	M 36x2	25	46	22x2,5
PA 525 AOS A	25	16	1"	M 42x2	30	50	27x2,5
PA 532 AOS A	32	20	1"1/4	M 52x2	38	60	33x2,5
PA 520 AOS 16 A	20	12	3/4"	M 30x2	20	40	17,5x2,5

PA 500 AOS 45 A

Complete interlock swage fitting 45° for HD 500

(EN 856 4SH), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zined, yellow passivated

Article category 1222



Designation

DN

size

inch

thread

tube-Ø

SW

O-ring


PA 520 AOS 45 A	20	12	3/4"	M 36x2	25	41	22x2,5
PA 520 AOS 1645 A	20	12	3/4"	M 30x2	20	36	17,5x2,5
PA 525 AOS 45 A	25	16	1"	M 42x2	30	50	27x2,5
PA 532 AOS 45 A	32	20	1"1/4	M 52x2	38	60	33x2,5

PA 500 AOS 90A

Complete interlock swage fitting 90° for HD 500

(EN 856 4SH), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zined, yellow passivated

Article category 1222



Designation

DN

size

inch

thread

tube-Ø

SW

O-ring


PA 520 AOS 1690 A	20	12	3/4"	M 30x2	20	36	17,5x2,5
PA 520 AOS 90 A	20	12	3/4"	M 36x2	25	41	22x2,5
PA 525 AOS 90 A	25	16	1"	M 42x2	30	50	27x2,5
PA 532 AOS 90 A	32	20	1"1/4	M 52x2	38	60	33x2,5

PA 700 AOS

Complete interlock swage fitting for HD 700

(SAE 100 R15), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zincd, yellow passivated

Article category 1222



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>	<i>O-ring</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------	---------------


PA 720 AOS 16	20	12	3/4"	M 30x2	20	36	17,5x2,5
PA 720 AOS	20	12	3/4"	M 36x2	25	41	22x2,5
PA 725 AOS	25	16	1"	M 42x2	30	50	27x2,5
PA 732 AOS	32	20	1"1/4	M 52x2	38	60	33x2,5

PA 700 AOS 45

Complete interlock swage fitting 45° for HD 700

(SAE 100 R15), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zined, yellow passivated

Article category 1222



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>	<i>O-ring</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------	---------------


PA 720 AOS 45	20	12	3/4"	M 36x2	25	41	22x2,5
PA 732 AOS 45	32	20	1"1/4	M 52x2	38	60	33x2,5
PA 720 AOS 1645	20	12	3/4"	M 30x2	20	36	17,5x2,5
PA 725 AOS 45	25	16	1"	M 42x2	30	50	27x2,5

PA 700 AOS 90

Complete interlock swage fitting 90° for HD 700

(SAE 100 R15), O-ring metric female 24° cone, heavy series (DKOS), material: steel, zined, yellow passivated

Article category 1222



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>	<i>O-ring</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------	---------------


PA 720 AOS 90	20	12	3/4"	M 36x2	25	41	22x2,5
PA 720 AOS 1690	20	12	3/4"	M 30x2	20	36	17,5x2,5
PA 725 AOS 90	25	16	1"	M 42x2	30	50	27x2,5
PA 732 AOS 90	32	20	1"1/4	M 52x2	38	60	33x2,5

PA 500 AOSS A

Complete interlock swage fitting for HD 500

O-ring seal, metric, super heavy series (DKOSS),
material: steel, zincd,
yellow passivated

Article category 1222



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>	<i>O-ring</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------	---------------

PA 525 AOSS A	25	16	1"	M 42x2	30	50	27x2,5
---------------	----	----	----	--------	----	----	--------


PA 532 AOSS A	32	20	1"1/4	M 52x2	38	60	33x2,5
---------------	----	----	-------	--------	----	----	--------

PA 500 AOSS 45 A

Complete interlock swage fitting 45° for HD 500

O-ring seal, metric, super heavy series (DKOSS), material: steel, zincd, yellow passivated

Article category 1222



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>	<i>O-ring</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------	---------------


PA 525 AOSS 45 A	25	16	1"	M 42x2	30	50	27x2,5
------------------	----	----	----	--------	----	----	--------

PA 500 AOSS 90 A

Complete interlock swage fitting 90° for HD 500

O-ring seal, metric, super heavy series (DKOSS),
material: steel, zincd,
yellow passivated

Article category 1222



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>	<i>O-ring</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------	---------------


PA 525 AOSS 90 A	25	16	1"	M 42x2	30	50	27x2,5
------------------	----	----	----	--------	----	----	--------

PA 500 AOS A H

Complete interlock swage fitting for HD 500

24° cone seat with O-ring, metric, heavy series (DKOS), for hammer application, material: steel, zincd, yellow passivated

Article category 1224



Designation

DN

size

inch

thread

tube-Ø

SW


PA 520 AOS A H	19	12	3/4"	M 36x2,0	25	46
PA 525 AOS A H	25	16	1"	M 52x2,0	30	50
PA 532 AOS A H	31	20	1"1/4	M 52x2,0	38	60

PA 400 FS

Complete swage fitting for HD 400

standpipe, heavy series (BES),
cutting ring connection,
material: steel, zincd,
yellow passivated

Article category 1225



Designation

DN

size

inch

tube-Ø


PA 406 FS	6	4	1/4"	10
PA 413 FS	13	8	1/2"	16
PA 416 FS	16	10	5/8"	20
PA 420 FS	20	12	3/4"	25
PA 425 FS	25	16	1"	30

PA 400 HL

Complete swage fitting for HD 400

male metric thread, 24° cone
seat, light series (CEL),
material: steel, zincd,
yellow passivated

Article category 1229



Designation

DN

size

inch

thread

tube-Ø

SW


PA 413 HL	13	8	1/2"	M 22x1,5	15	22
PA 416 HL	16	10	5/8"	M 26x1,5	18	27
PA 420 HL	20	12	3/4"	M 30x2	22	30

PA 400 HS

Complete swage fitting for HD 400

male metric thread, heavy series
(CES), 24° cone seat,
material: steel, zincd,
yellow passivated

Article category 1230



Designation

DN

size

inch

thread

tube-Ø

SW

PA 406 HS	6	4	1/4"	M 18x1,5	10	19
PA 410 HS	10	6	3/8"	M 22x1,5	14	22
PA 410 HS 08	10	6	3/8"	M 20x1,5	12	22
PA 413 HS	13	8	1/2"	M 24x1,5	16	24
PA 416 HS	16	10	5/8"	M 30x2	20	30
PA 420 HS	20	12	3/4"	M 36x2	25	36
PA 420 HS 16	20	12	3/4"	M 30x2	20	30
PA 425 HS	25	16	1"	M 42x2	30	46
PA 425 HS 20	25	16	1"	M 36x2	25	36
PA 425 HS 32	25	16	1"	M 52x2	38	55

PA 400 HS 45

Complete swage fitting 45°
for HD 400

male metric thread, heavy series
(CES), 24° cone seat,
material: steel, zincd,
yellow passivated

Article category 1230



Designation

DN

size

inch

thread

tube-Ø

PA 425 HS 45

25

16

1"

M 42x2

30

PA 400 HS 90

Complete swage fitting 90°
for HD 400

male metric thread, heavy series
(CES), 24° cone seat,
material: steel, zincd,
yellow passivated

Article category 1230



Designation

DN

size

inch

thread

tube-Ø

PA 425 HS 90

25

16

1"

M 42x2


30

PA 500 HS

Complete swage fitting for HD 500

male metric thread, heavy series
(CES), 24° cone seat,
material: steel, zincd,
yellow passivated

Article category 1230



Designation

DN

size

inch

thread

tube-Ø

SW

PA 525 HS

25

16

1"

M 42x2

30

46

PA 532 HS

32

20

1"1/4

M 52x2

38


55

PA 700 HS

Complete interlock swage fitting for HD 700

male metric thread, heavy series (CES), 24° cone seat, material: steel, zincd, yellow passivated

Article category 1230



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------


PA 720 HS	20	12	3/4"	M 36x2	25	36
PA 720 HS 16	20	12	3/4"	M 30x2	20	30
PA 725 HS	25	16	1"	M 42x2	30	46
PA 732 HS	32	20	1"1/4	M 52x2	38	55

PA 500 HS A

Complete interlock swage fitting for HD 500

male metric thread, heavy series (CES), 24° cone seat, material: steel, zincd, yellow passivated

Article category 1230



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>tube-Ø</i>	<i>SW</i>
--------------------	-----------	-------------	-------------	---------------	---------------	-----------


PA 520 HS 16 A	20	12	3/4"	M 30x2	20	30
PA 520 HS A	20	12	3/4"	M 36x2	25	36
PA 525 HS A	25	16	1"	M 42x2	30	46
PA 532 HS A	31	20	1"1/4	M 52x2	38	55

PA 400 HF

Swage fitting, French series

for HD 400, male thread
connection 24°, French series,
material: steel, zincd,
yellow passivated

Article category 1232



Designation

DN

size

inch

thread

tube-Ø

SW


PA 410 HF	9,5	6	3/8"	20x1,5	13,25	22
PA 413 HF	12	8	1/2"	24x1,5	16,75	27
PA 416 HF	16	10	5/8"	30x1,5	21,25	32
PA 420 HF	19	12	3/4"	36x1,5	26,75	36
PA 425 HF	25	16	1"	45x1,5	33,50	46

PA 400 AF

Complete swage fitting, French series

for HD 400, 24° seal, connection
suitable for French series,
material: steel, zincd,
yellow passivated

Article category 1232



Designation

DN

size

inch

thread

tube-Ø


PA 410 AF	10	6	3/8"	20x1,5	13,25
PA 413 AF	13	8	1/2"	24x1,5	16,75
PA 416 AF	16	10	5/8"	30x1,5	21,25
PA 420 AF	20	12	3/4"	36x1,5	26,75
PA 425 AF	25	16	1"	45x1,5	33,5

PA 400 AF 45

Complete swage fitting 45°, French series

for HD 400 24° seal, connection
suitable for French series,
material: steel, zincd,
yellow passivated

Article category 1232



Designation

DN

size

inch

thread

tube-Ø

PA 413 AF 45

13

8

1/2"

24x1,5

16,75

PA 416 AF 45

16

10

5/8"

30x1,5

21,25

PA 400 AF 90

Complete swage fitting 90°,
French series for HD 400

24° seal, connection suitable for
French series, material: steel,
zincd, yellow passivated

Article category 1232



Designation

DN

size

inch

thread

tube-Ø


PA 413 AF 90	13	8	1/2"	24x1,5	16,75
PA 416 AF 90	16	10	5/8"	30x1,5	21,25
PA 420 AF 90	20	12	3/4"	36x1,5	26,75

PA 400 SPF

Complete swage fitting for HD 400

Poclair 4-hole fast flange,
material: steel, zined,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size


PA 413 SPF	13	8	1/2"	1/2"
PA 416 SPF	16	10	5/8"	5/8"
PA 420 SPF	20	12	3/4"	3/4"
PA 425 SPF	25	16	1"	1"

PA 500 SPF

Complete swage fitting for HD 500

Poclain 4-hole fast flange,
material: steel, zined,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size

PA 532 SPF

32

20

1"1/4

1"1/4

PA 400 SPF Q

Complete swage fitting for HD 400

Poclain 4-hole square flange,
material: steel, zincd, yellow
passivated

Article category 1235



Designation

DN

size

inch

flange size

PA 425 SPF Q

25

16

1"


1"

PA 400 SPL

Complete swage fitting for HD 400

Poclair 4-hole loose flange,
material: steel, zincd,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size


PA 413 SPL	13	8	1/2"	1/2"
PA 416 SPL	16	10	5/8"	5/8"
PA 420 SPL	20	12	3/4"	3/4"
PA 425 SPL	25	16	1"	1"

PA 400 SPL 90

Complete swage fitting for HD 400

Poclair 4-hole loose flange 90°,
material: steel, zincd,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size

PA 413 SPL 90

13

8

1/2"

1/2"

PA 416 SPL 90

16

10

5/8"

5/8"

PA 420 SPL 90

20

12

3/4"

3/4"

PA 425 SPL 90

25

16

1"


1"

PA 500 SPL

Complete swage fitting for HD 500

Poclain 4-hole loose flange,
material: steel, zincd,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size

PA 532 SPL

32

20

1"1/4


1"1/4

PA 500 SPL 90

Complete swage fitting for HD 500

Poclain 4-hole loose flange 90°,
material: steel, zincd,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size

PA 532 SPL 90

32

20

1"1/4

1"1/4

PA 400 SPL Q

Complete swage fitting for HD 400

Poclair 4-hole loose flange,
square, material: steel, zincd,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size

PA 425 SPL Q

25

16

1"

1"

PA 400 SPL 90Q

Complete swage fitting for HD 400

Poclair 4-hole loose flange 90°,
square, material: steel, zined,
yellow passivated

Article category 1235



Designation

DN

size

inch

flange size

PA 425 SPL 90 Q

25

16

1"


1"

PA 400 AJ

Complete swage fitting for HD 400

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW


PA 410 AJ	10	6	3/8"	9/16"-18	19
PA 410 AJ 13	10	6	3/8"	3/4"-16	24
PA 413 AJ	13	8	1/2"	3/4"-16	24
PA 413 AJ 16	13	8	1/2"	7/8"-14	27
PA 413 AJ 20	13	8	1/2"	1"1/16-12	32
PA 416 AJ	16	10	5/8"	7/8"-14	27
PA 416 AJ 20	16	10	5/8"	1"1/16-20	32
PA 420 AJ 14	20	12	3/4"	1"3/16-12	36
PA 420 AJ	20	12	3/4"	1"1/16-12	32
PA 420 AJ 25	20	12	3/4"	1"5/16-12	41
PA 425 AJ	25	16	1"	1"5/16-12	41

PA 400 AJ 45

Complete swage fitting 45° for HD 400

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>SW</i>
--------------------	-----------	-------------	-------------	---------------	-----------


PA 410 AJ 45	10	6	3/8"	9/16"-18	19
PA 410 AJ 13 45	10	6	3/8"	3/4"-16	24
PA 413 AJ 45	13	8	1/2"	3/4"-16	24
PA 413 AJ 16 45	13	8	1/2"	7/8"-14	27
PA 416 AJ 45	16	10	5/8"	7/8"-14	27
PA 416 AJ 20 45	16	10	5/8"	1"1/16-12	32
PA 420 AJ 45	20	12	3/4"	1"1/16-12	32
PA 425 AJ 45	25	16	1"	1"5/16-12	41

PA 400 AJ 90

Complete swage fitting 90°
or HD 400

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



Designation	DN	size	inch	thread	SW	L
-------------	----	------	------	--------	----	---


PA 410 AJ 90	10	6	3/8"	9/16"-18	19	-
PA 410 AJ 13 90	10	6	3/8"	3/4"-16	24	-
PA 410 AJ 90 L 82	10	6	3/8"	9/16"-18	19	82
PA 413 AJ 90	13	8	1/2"	3/4"-16	24	-
PA 413 AJ 16 90	13	8	1/2"	7/8"-14	27	-
PA 413 AJ 90 L 92	13	8	1/2"	3/4"-16	24	92
PA 416 AJ 90	16	10	5/8"	7/8"-14	27	-
PA 416 AJ 20 90	16	10	5/8"	1"1/16	32	-
PA 420 AJ 90	20	12	3/4"	1"1/16-12	32	-
PA 420 AJ 90 L 92	20	12	3/4"	1"1/16-12	32	92
PA 420 AJ 90 L 95	20	12	3/4"	1"1/16-12	32	95
PA 420 AJ 25 90	20	12	3/4"	1"5/16-12	41	-
PA 425 AJ 90	25	16	1"	1"5/16-12	41	-

PA 500 AJ

Complete swage fitting for HD 500

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW

PA 532 AJ

32

20

1"1/4

1"5/8 -12

50

PA 540 AJ

40

24

1"1/2

1"7/8 -12

55

PA 550 AJ

50

32

2"

2"1/2 -12


70

PA 500 AJ A

Complete interlock swage fitting for HD 500

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>SW</i>
--------------------	-----------	-------------	-------------	---------------	-----------


PA 520 AJ A	20	12	3/4"	1"1/16-12	32
PA 525 AJ A	25	16	1"	1"5/16-12	41
PA 532 AJ A	32	20	1"1/4	1"5/8-12	50
PA 532 AJ 40 A	32	20	1"1/4	1"7/8-12	55
PA 540 AJ A	40	24	1"1/2	1"7/8"-12	55
PA 550 AJ A	50	32	2"	2"1/2-12	70

PA 500 AJ 45

Complete swage fitting 45° for HD 500

JIC female 74° cone seat,
material: steel, zincd, yellow
passivated

Article category 1236



Designation

DN

size

inch

thread

SW


PA 532 AJ 45	32	20	1"1/4	1"5/8 -12	50
PA 540 AJ 45	40	24	1"1/2	1"7/8-12	55
PA 550 AJ 45	50	32	2"	2"1/2 -12	70

PA 500 AJ 45 A

Complete interlock swage fitting 45° for HD 500

JIC female 74° cone seat, material: steel, zincd, yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW


PA 520 AJ 45 A	19	12	3/4"	1"1/16-12	32
PA 525 AJ 45 A	25	16	1"	1"5/16-12	41
PA 532 AJ 45 A	32	20	1"1/4	1"5/8-12	50
PA 540 AJ 45 A	40	24	1"1/2	1"7/8-12	55
PA 550 AJ 45 A	50	32	2"	2"1/2-12	70

PA 500 AJ 90

Complete swage fitting 90° for HD 500

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW

PA 532 AJ 90

32

20

1"1/4

1"5/8-12

50

PA 540 AJ 90

40

24

1"1/2

1"7/8 -12

55

PA 550 AJ 90

50

32

2"

2"1/2 -12


70

PA 500 AJ 90 A

Complete interlock swage fitting 90° for HD 500

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW


PA 520 AJ 90 A	20	12	3/4"	1"1/16 -12	32
PA 525 AJ 90 A	25	16	1"	1"5/16/12	41
PA 532 AJ 90 A	32	20	1"1/4	1"5/8 -12	50
PA 540 AJ 90 A	40	24	1"1/2	1"7/8 -12	55
PA 550 AJ 90 A	50	32	2"	2"1/2 -12	70

PA 700 AJ

Complete interlock swage fitting for HD 700

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW


PA 720 AJ	20	12	3/4"	1"1/16-12	32
PA 725 AJ	25	16	1"	15/16"-12	41
PA 732 AJ	32	20	1"1/4	1"5/8-12	50
PA 732 AJ 40	32	20	1"1/4	1"7/8-12	55
PA 740 AJ	40	24	1"1/2	1"7/8-12	55
PA 740 AJ 50	40	24	1"1/2	2"1/2-12	70

PA 700 AJ 45

Complete interlock swage fitting 45° for HD 700

JIC female 74° cone seat,
material: steel, zincd,
yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW


PA 720 AJ 45	20	12	3/4"	1"1/16-12	32
PA 725 AJ 45	25	16	1"	1"5/16-12	41
PA 732 AJ 45	32	20	1"1/4	1"5/8-12	50
PA 740 AJ 45	40	24	1"1/2	1"7/8-12	55

PA 700 AJ 90

Complete interlock swage fitting 90° for HD 700

JIC female 74° cone seat
material: steel, zincd,
yellow passivated

Article category 1236



Designation

DN

size

inch

thread

SW


PA 720 AJ 90	20	12	3/4"	1"1/16-12	32
PA 725 AJ 90	25	16	1"	1"5/16/12	41
PA 725 AJ 32 90	25	16	1"	1"5/8-12	50
PA 732 AJ 90	32	20	1"1/4	1"5/8 -12	50
PA 732 AJ 40 90	32	20	1"1/4	1"7/8-12	55
PA 740 AJ 90	40	24	1"1/2	1"7/8 -12	55
PA 740 AJ 50 90	40	24	1"1/2	2"1/2-12	70

PA 500 A0J A

Complete interlock swage fitting for HD 500

O-ring, JIC female 74° cone seat, material: steel, zincd, yellow passivated

Article category 1237



Designation

DN

size

inch

thread

SW


PA 520 A0J A	20	12	3/4"	1"1/16-12	32
PA 525 A0J A	25	16	1"	1"5/16-12	41
PA 532 A0J A	32	20	1"1/4	1"5/8-12	50
PA 540 A0J A	40	24	1"1/2	1"7/8-12	55
PA 550 A0J A	50	32	2"	2"1/2-12	70

PA 500 A0J 45 A

Complete interlock swage fitting 45° for HD 500

O-ring, JIC female 74° cone seat, material: steel, zincd, yellow passivated

Article category 1237



Designation

DN

size

inch

thread

SW


PA 520 A0J 45 A	20	12	3/4"	1"1/16-12	32
PA 525 A0J 45 A	25	16	1"	1"5/16-12	41
PA 532 A0J 45 A	32	20	1"1/4	1"5/8-12	50
PA 540 A0J 45 A	40	24	1"1/2	1"7/8-12	55
PA 550 A0J 45 A	50	32	2"	2"1/2-12	70

PA 500 A0J 90 A

Complete interlock swage fitting 90° for HD 500

O-ring, JIC female 74° cone seat, material: steel, zincd, yellow passivated

Article category 1237



Designation

DN

size

inch

thread

SW


PA 520 A0J 90 A	20	12	3/4"	1"1/16-12	32
PA 525 A0J 90 A	25	16	1"	1"5/16-12	41
PA 532 A0J 90 A	32	20	1"1/4	1"5/8-12	50
PA 540 A0J 90 A	40	24	1"1/2	1"7/8-12	55
PA 550 A0J 90 A	50	32	2"	2"1/2-12	70

PA 700 A0J

Complete interlock swage fitting for HD 700

O-ring, JIC female 74° cone seat, material: steel, zincd, yellow passivated

Article category 1237



Designation

DN

size

inch

thread

SW


PA 720 A0J	20	12	3/4"	1"1/16-12	32
PA 725 A0J	25	16	1"	1"5/16-12	41
PA 732 A0J	32	20	1"1/4	1"5/8-12	50
PA 740 A0J	40	24	1"1/2	1"7/8-12	55

PA 700 A0J 45

Complete interlock swage fitting 45° for HD 700

O-ring, JIC female 74° cone seat, material: steel, zincd, yellow passivated

Article category 1237



Designation

DN

size

inch

thread

SW


PA 720 A0J 45	20	12	3/4"	1"1/16-12	32
PA 725 A0J 45	25	16	1"	1"5/16-12	41
PA 732 A0J 45	32	20	1"1/4	1"5/8-12	50
PA 740 A0J 45	40	24	1"1/2	1"7/8-12	55

PA 700 A0J 90

Complete interlock swage fitting 90° for HD 700

O-ring, JIC female 74° cone seat, material: steel, zincd, yellow passivated

Article category 1237



Designation

DN

size

inch

thread

SW


PA 720 A0J 90	20	12	3/4"	1"1/16-12	32
PA 725 A0J 90	25	16	1"	1"5/16-12	41
PA 732 A0J 90	32	20	1"1/4	1"5/8-12	50
PA 740 A0J 90	40	24	1"1/2	1"7/8-12	55

PA 400 HJ

Complete swage fitting for HD 400

male UNF thread and 74° cone
seat, material: steel, zincd,
yellow passivated

Article category 1240



Designation

DN

size

inch

thread


PA 410 HJ	10	6	3/8"	9/16"-18
PA 413 HJ	13	8	1/2"	3/4"-16
PA 413 HJ 16	13	8	1/2"	3/4"-16
PA 413 HJ 20	12	8	1/2"	1"1/16-12
PA 416 HJ	16	10	5/8"	7/8"-14
PA 416 HJ 20	16	10	5/8"	1"1/16-12
PA 420 HJ 14	20	12	3/4"	1"3/16-12
PA 420 HJ	20	12	3/4"	1"1/16-12
PA 420 HJ 25	20	12	3/4"	1"5/16-12
PA 425 HJ	25	16	1"	1"5/16-12

PA 500 HJ

Complete swage fitting for HD 500

male UNF thread and 74° cone
seat, material: steel, zincd,
yellow passivated

Article category 1240



Designation

DN

size

inch

thread

PA 532 HJ

32

20

1"1/4

1"5/8-12

PA 540 HJ

40

24

1"1/2

1"7/8-12

PA 550 HJ

50

32

2"


2"1/2-12

PA 500 HJ A

Complete interlock swage fitting for HD 500

male UNF thread and 74° cone seat, material: steel, zincd, yellow passivated

Article category 1240



Designation

DN

size

inch

thread


PA 520 HJ A	20	12	3/4"	1"1/16-12
PA 525 HJ A	25	16	1"	1"5/16-12
PA 532 HJ A	32	20	1"1/4	1"5/8-12
PA 540 HJ A	40	24	1"1/2	1"7/8-12
PA 540 HJ 50 A	40	24	1"1/2	2"1/2-12
PA 550 HJ A	50	32	2"	2"1/2-12

PA 600 HJ

Complete swage fitting for HD 600

male UNF thread and 74° cone
seat, material: steel, zincd,
yellow passivated

Article category 1240



Designation

DN

size

inch

thread

PA 650 HJ

5

32

2"


2"1/2-12

PA 700 HJ

Complete interlock swage fitting for HD 700

male UNF thread and 74° cone seat, material: steel, zincd, yellow passivated

Article category 1240



Designation

DN

size

inch

thread


PA 720 HJ	20	12	3/4"	1"1/16-12
PA 725 HJ	25	16	1"	1"5/16-12
PA 732 HJ	32	20	1"1/4	1"5/8-12
PA 732 HJ 40	32	20	1"1/4	1"7/8-12
PA 740 HJ	40	24	1"1/2	1"7/8-12
PA 740 HJ 50	40	24	1"1/2	2"1/2-12

PA 400 HN

Complete swage fitting for HD 400

male NPTF thread (AGN),
material: steel, zincd,
yellow passivated

Article category 1243



Designation

DN

size

inch

thread


PA 410 HN	10	6	3/8"	3/8"-18
PA 413 HN	13	8	1/2"	1/2"-14
PA 420 HN	20	12	3/4"	3/4"-14
PA 425 HN	25	16	1"	1"-11,5
PA 425 HN 32	25	16	1"	1"1/4-11,5

PA 500 HN

Complete swage fitting for HD 500

male NPTF thread (AGN),
material: steel, zincd,
yellow passivated

Article category 1243



Designation

DN

size

inch

thread


PA 532 HN	32	20	1"1/4	1"1/4-11,5
PA 540 HN	40	24	1"1/2	1"1/2-11,5
PA 550 HN	50	32	2"	2"-11,5

PA 500 HN A

Complete interlock swage fitting for HD 500

male NPTF thread (AGN),
material: steel, zincd,
yellow passivated

Article category 1243



Designation

DN

size

inch

thread


PA 520 HN A	20	12	3/4"	3/4"-14
PA 525 HN 32 A	25	16	1"	1"1/4-11,5
PA 525 HN A	25	16	1"	1"-11,5
PA 532 HN A	32	20	1"1/4	1"1/4-11,5
PA 532 HN 40 A	32	20	1"1/4	1"1/2-11,5
PA 540 HN A	40	24	1"1/2	1"1/2-11,5
PA 540 HN 50 A	40	24	1"1/2	2"-11,5
PA 550 HN A	50	32	2"	2"-11,5

PA 600 HN

Complete interlock swage fitting for HD 600

male NPTF thread (AGN),
material: steel, zincd,
yellow passivated

Article category 1243



Designation

DN

size

inch

thread

PA 650 HN

50

32

2"


2"-11,5

PA 700 HN

Complete interlock swage fitting for HD 700

NPTF male fitting with 60° cone seat (AGN), material: steel, zincd, yellow passivated

Article category 1243



Designation

DN

size

inch

thread


PA 720 HN	20	12	3/4"	3/4"-14
PA 725 HN	25	16	1"	1"-11,5
PA 725 HN 32	25	16	1"	1"1/4-11,5
PA 732 HN	32	20	1"1/4	1"1/4-11,5
PA 732 HN 40	32	20	1"1/4	1"1/2-11,5
PA 740 HN	40	24	1"1/2	1"1/2-11,5
PA 740 HN 50	40	24	1"1/2	2"-11,5

PA 400 SF

Complete swage fitting for HD 400,

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 413 SF	13	8	1/2"	1/2"	30,2
PA 413 SF 20	13	8	1/2"	3/4"	38,1
PA 413 SF 25	13	8	1/2"	1"	44,4
PA 416 SF 20	16	10	5/8"	3/4"	38,1
PA 416 SF 25	16	10	5/8"	1"	44,4
PA 420 SF	20	12	3/4"	3/4"	38,1
PA 420 SF 25	20	12	3/4"	1"	44,4
PA 420 SF 32	20	12	3/4"	1"1/4	50,8
PA 420 SF 40	20	12	3/4"	1"1/2	60,3
PA 425 SF 20	25	16	1"	3/4"	38,1
PA 425 SF	25	16	1"	1"	44,4
PA 425 SF 32	25	16	1"	1"1/4	50,8
PA 425 SF 40	25	16	1"	1"1/2	60,3
PA 425 SF 50	25	16	1"	2"	71,4

PA 400 SF 45

Complete swage fitting 45°
for HD 400,

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 413 SF 45	13	8	1/2"	1/2"	30,2
PA 413 SF 25 45	13	8	1/2"	1"	44,4
PA 416 SF 20 45	16	10	5/8"	3/4"	38,1
PA 416 SF 25 45	16	10	5/8"	1"	44,4
PA 420 SF 45	20	12	3/4"	3/4"	38,1
PA 420 SF 25 45	20	12	3/4"	1"	44,4
PA 420 SF 32 45	20	12	3/4"	1"1/4	50,8
PA 420 SF 40 45	20	12	3/4"	1"1/2	60,3
PA 425 SF 20 45	25	16	1"	3/4"	38,1
PA 425 SF 45	25	16	1"	1"	44,4
PA 425 SF 32 45	25	16	1"	1"1/4	50,8
PA 425 SF 40 45	25	16	1"	1"1/2	60,3
PA 425 SF 50 45	25	16	1"	2"	71,4

PA 400 SF 90

Complete swage fitting 90°
for HD 400,

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D

L


PA 413 SF 90	13	8	1/2"	1/2"	30,2	-
PA 413 SF 90 L 83	13	8	1/2"	1/2"	30,2	83
PA 413 SF 20 90	13	8	1/2"	3/4"	38,1	-
PA 413 SF 20 90 L 85	13	8	1/2"	3/4"	38,1	85
PA 413 SF 25 90	13	8	1/2"	1"	44,4	-
PA 416 SF 20 90	16	10	5/8"	3/4"	38,1	-
PA 416 SF 25 90	16	10	5/8"	1"	44,4	-
PA 420 SF 90	20	12	3/4"	3/4"	38,1	-
PA 420 SF 90 L 100	20	12	3/4"	3/4"	38,1	100
PA 420 SF 90 L 120	20	12	3/4"	3/4"	38,1	120
PA 420 SF 90 L 127	20	12	3/4"	3/4"	38,1	127
PA 420 SF 90 L 95	20	12	3/4"	3/4"	38,1	95
PA 420 SF 25 90	20	12	3/4"	1"	44,4	-
PA 420 SF 25 90 L 82	20	12	3/4"	1"	44,4	82
PA 420 SF 32 90	20	12	3/4"	1"1/4	50,8	-
PA 420 SF 40 90	20	12	3/4"	1"1/2	60,3	-
PA 425 SF 20 90	25	16	1"	3/4"	38,1	-
PA 425 SF 90	25	16	1"	1"	44,4	-
PA 425 SF 90 L 120	25	16	1"	1"	44,4	120
PA 425 SF 32 90	25	16	1"	1"1/4	50,8	-
PA 425 SF 32 90 L 100	25	16	1"	1"1/4	50,8	100
PA 425 SF 40 90	25	16	1"	1"1/2	60,3	-
PA 425 SF 50 90	25	16	1"	2"	71,4	-

PA 500 SF

Complete swage fitting
for HD 500,

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 525 SF	25	16	1"	1"	44,4
PA 525 SF 32	25	16	1"	1"1/4	50,8
PA 532 SF 25	32	20	1"1/4	1"	44,4
PA 532 SF	32	20	1"1/4	1"1/4	50,8
PA 532 SF 40	32	20	1"1/4	1"1/2	60,3
PA 540 SF	40	24	1"1/2	1"1/2	60,3
PA 540 SF 50	40	24	1"1/2	2"	60,3
PA 550 SF	50	32	2"	2"	71,4
PA 532 SF 67	32	20	1"1/4	1"1/4	50,8

PA 500 SF A

Complete interlock swage fitting for HD 500

SAE flange connection, 3000 psi (SFL), material: steel, zincd, yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF A	20	12	3/4"	3/4"	38,1
PA 520 SF 25 A	20	12	3/4"	1"	44,4
PA 525 SF A	25	16	1"	1"	44,4
PA 525 SF 32 A	25	16	1"	1"1/4	50,8
PA 532 SF A	32	20	1"1/4	1"1/4	50,8
PA 532 SF 40 A	32	20	1"1/4	1"1/2	60,3
PA 540 SF A	40	24	1"1/2	1"1/2	60,3
PA 540 SF 50 A	40	24	1"1/2	2"	71,4
PA 550 SF A	50	32	2"	2"	71,4

PA 500 SF 45

Complete swage fitting 45° for HD 500

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 525 SF 45	25	16	1"	1"	44,4
PA 525 SF 32 45	25	16	1"	1"1/4	50,8
PA 532 SF 25 45	32	20	1"1/4	1"	44,4
PA 532 SF 45	32	20	1"1/4	1"1/4	50,8
PA 532 SF 40 45	32	20	1"1/4	1"1/2	60,3
PA 540 SF 45	40	24	1"1/2	1"1/2	60,3
PA 540 SF 50 45	40	24	1"1/2	2"	71,4
PA 550 SF 40 45	50	32	2"	1"1/2	60,3
PA 550 SF 45	50	32	2"	2"	71,4

PA 500 SF 45 A

Complete interlock swage fitting 45° for HD 500

SAE flange connection, 3000 psi (SFL), material: steel, zincd, yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 45 A	20	12	3/4"	3/4"	28,1
PA 520 SF 25 45 A	20	12	3/4"	1"	44,4
PA 525 SF 45 A	25	16	1"	1"	44,4
PA 525 SF 32 45 A	25	16	1"	1 1/4"	50,8
PA 532 SF 45 A	32	20	1 1/4"	1 1/4"	50,8
PA 532 SF 40 45 A	32	20	1 1/4"	1 1/2"	60,3
PA 540 SF 45 A	40	24	1 1/2"	1 1/2"	60,3
PA 540 SF 50 45 A	40	24	1 1/2"	2"	71,4
PA 550 SF 45 A	50	32	2"	2"	71,4

PA 500 SF 90

Complete swage fitting 90° for HD 500

SAE flange connection 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 525 SF 90	25	16	1"	1"	44,4
PA 525 SF 32 90	25	16	1"	1"1/4	50,8
PA 532 SF 25 90	32	20	1"1/4	1"	44,4
PA 532 SF 90	32	20	1"1/4	1"1/4	50,8
PA 532 SF 40 90	32	20	1"1/4	1"1/2	60,3
PA 540 SF 90	40	24	1"1/2	1"1/2	60,3
PA 540 SF 50 90	40	24	1"1/2	2"	71,4
PA 550 SF 40 90	50	32	2"	1"1/2	60,3
PA 550 SF 90	50	32	2"	2"	71,4

PA 500 SF 90 A

Complete interlock swage fitting 90° for HD 500

SAE flange connection, 3000 psi (SFL), material: steel, zincd, yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 90 A	20	12	3/4"	3/4"	38,1
PA 520 SF 25 90 A	20	12	3/4"	1"	44,4
PA 525 SF 90 A	25	16	1"	1"	44,4
PA 525 SF 32 90 A	25	16	1"	1"1/4	50,8
PA 532 SF 90 A	32	20	1"1/4	1"1/4	50,8
PA 532 SF 40 90 A	32	20	1"1/4	1"1/2	60,3
PA 540 SF 90 A	40	24	1"1/2	1"1/2	60,3
PA 540 SF 50 90 A	40	24	1"1/2	2"	71,4
PA 550 SF 90 A	50	32	2"	2"	71,4

PA 600 SF

Complete interlock swage fitting for HD 600

SAE flange connection, 3000 psi (SFL), material: steel, zincd, yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D

PA 650 SF

50

32

2"

2"


71,4

PA 600 SF 45

Complete swage fitting 45° for HD 600

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D

PA 650 SF 45

50

32

2"

2"


71,4

PA 600 SF 90

Complete swage fitting 90°
for HD 600

SAE flange connection, 3000 psi,
material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D

PA 650 SF 90

50

32

2"

2"


71,4

PA 700 SF

Complete interlock swage fitting for HD 700

SAE flange connection, 3000 psi (SFL), material: steel, zincd, yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 720 SF	20	12	3/4"	3/4"	38,1
PA 720 SF 25	20	12	3/4"	1"	44,4
PA 725 SF	25	16	1"	1"	44,4
PA 725 SF 32	25	16	1"	1"1/4	50,8
PA 732 SF	32	20	1"1/4	1"1/4	50,8
PA 732 SF 40	32	20	1"1/4	1"1/2	60,3
PA 740 SF	40	24	1"1/2	1"1/2	60,3
PA 740 SF 50	40	24	1"1/2	2"	71,4

PA 700 SF 45

Complete swage fitting 45°
for HD 700

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 720 SF 45	20	12	3/4"	3/4"	38,1
PA 720 SF 25 45	20	12	3/4"	1"	44,4
PA 725 SF 45	25	16	1"	1"	44,4
PA 725 SF 32 45	25	16	1"	1"1/4	50,8
PA 732 SF 45	32	20	1"1/4	1"1/4	50,8
PA 732 SF 40 45	32	20	1"1/4	1"1/2	60,3
PA 740 SF 45	40	24	1"1/2	1"1/2	60,3
PA 740 SF 50 45	40	24	1"1/2	2"	71,4

PA 700 SF 90

Complete swage fitting 90° for HD 700

SAE flange connection, 3000 psi
(SFL), material: steel, zincd,
yellow passivated

Article category 1244



Designation

DN

size

inch

flange size (inch)

D


PA 720 SF 90	20	12	3/4"	3/4"	38,1
PA 725 SF 90	25	16	1"	1"	44,4
PA 725 SF 32 90	25	16	1"	1"1/4	50,8
PA 732 SF 90	32	20	1"1/4	1"1/4	50,8
PA 732 SF 40 90	32	20	1"1/4	1"1/2	60,3
PA 740 SF 90	40	24	1"1/2	1"1/2	60,3
PA 740 SF 50 90	40	24	1"1/2	2"	71,4
PA 720 SF 25 90	20	12	3/4"	1"	44,4

PA 400 SF 6

Complete swage fitting for HD 400,

SAE flange connection, 6000 psi
(SFS), material: steel, zincd,
yellow passivated

Article category 1245



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>flange size (inch)</i>	<i>D</i>
--------------------	-----------	-------------	-------------	---------------------------	----------


PA 413 SF 6	13	8	1/2"	1/2"	31,7
PA 413 SF 6 20	13	8	1/2"	3/4"	41,3
PA 413 SF 6 25	13	8	1/2"	1"	47,6
PA 416 SF 6 13	16	10	5/8"	1/2"	31,7
PA 416 SF 6 20	16	10	5/8"	3/4"	41,3
PA 416 SF 6 25	16	10	5/8"	1"	47,6
PA 420 SF 6 13	20	12	3/4"	1/2"	31,7
PA 420 SF 6	20	12	3/4"	3/4"	41,3
PA 420 SF 6 25	20	12	3/4"	1"	47,6
PA 420 SF 6 32	20	12	3/4"	1"1/4	54,0
PA 425 SF 6 20	25	16	1"	3/4"	41,3
PA 425 SF 6	25	16	1"	1"	47,6
PA 425 SF 6 32	25	16	1"1/4	1"	54,0
PA 425 SF 6 40	25	16	1"	1"1/2	63,5
PA 420 SF 6 22	20	12	3/4"	3/4"	41,3

PA 400 SF 6 45

Complete swage fitting 45°
for HD 400,

SAE flange connection, 6000 psi
(SFS), material: steel, zincd,
yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D

L


PA 413 SF 6 45	13	8	1/2"	1/2"	31,7	-
PA 413 SF 6 20 45	13	8	1/2"	3/4"	41,3	-
PA 413 SF 6 20 45 L 50	13	8	1/2"	3/4"	41,3	50
PA 413 SF 6 25 45	13	8	1/2"	1"	47,6	-
PA 416 SF 6 13 45	16	10	5/8"	1/2"	31,7	-
PA 416 SF 6 20 45	16	10	5/8"	3/4"	41,3	-
PA 416 SF 6 20 45 L 75	16	10	5/8"	3/4"	41,3	75
PA 416 SF 6 25 45	16	10	5/8"	1"	47,6	-
PA 420 SF 6 13 45	20	12	3/4"	1/2"	31,7	-
PA 420 SF 6 45	20	12	3/4"	3/4"	41,3	-
PA 420 SF 6 45 L 52	20	12	3/4"	3/4"	41,3	52
PA 420 SF 6 45 L 75	20	12	3/4"	3/4"	41,3	75
PA 420 SF 6 45 L 100	20	12	3/4"	3/4"	41,3	100
PA 420 SF 6 25 45	20	12	3/4"	1"	47,6	-
PA 420 SF 6 32 45	20	12	3/4"	1"1/4	54,0	-
PA 425 SF 6 20 45	25	16	1"	3/4"	41,3	-
PA 425 SF 6 45	25	16	1"	1"	47,6	-
PA 425 SF 6 45 L 100	25	16	1"	1"	47,6	100
PA 425 SF 6 45 L 150	25	16	1"	1"	47,6	150
PA 425 SF 6 45 L 60	25	16	1"	1"	47,6	60
PA 425 SF 6 40 45	25	16	1"	1"1/2	63,5	-
PA 425 SF 6 32 45	25	16	1"	1"1/4	54,0	-
PA 425 SF 6 32 45 L 75	25	16	1"	1"1/4	54,4	75

PA 400 SF 6 90

Complete swage fitting 90° for HD 400

SAE flange connection, 6000 psi
(SFS); material: steel, zincd,
yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D

L

PA 413 SF 6 90	13	8	1/2"	1/2"	31,7	-
PA 413 SF 6 20 90	13	8	1/2"	3/4"	41,3	-
PA 413 SF 6 25 90	13	8	1/2"	1"	47,6	-
PA 416 SF 6 13 90	16	10	5/8"	1/2"	31,7	-
PA 416 SF 6 20 90	16	10	5/8"	3/4"	41,3	-
PA 416 SF 6 20 90 L 85	16	10	5/8"	3/4"	41,3	85
PA 416 SF 6 25 90	16	10	5/8"	1"	47,6	-
PA 416 SF 6 25 90 L 86	16	10	5/8"	1"	47,6	86
PA 416 SF 6 25 90 L 100	16	10	5/8"	1"	47,6	-
PA 416 SF 6 32 90 L 100	16	10	5/8"	1"1/4	54,0	-
PA 420 SF 6 13 90	20	12	3/4"	1/2"	31,7	-
PA 420 SF 6 13 90 L 80	20	12	3/4"	1/2"	31,7	80
PA 420 SF 6 13 90 L 100	20	12	3/4"	1/2"	31,7	-
PA 420 SF 6 90	20	12	3/4"	3/4"	41,3	-
PA 420 SF 6 90 L 85	20	12	3/4"	3/4"	41,3	85
PA 420 SF 6 90 L 100	20	12	3/4"	3/4"	41,3	100
PA 420 SF 6 90 L 150	20	12	3/4"	3/4"	41,3	150
PA 420 SF 6 25 90	20	12	3/4"	1"	47,6	-
PA 420 SF 6 32 90	20	12	3/4"	1"1/4	54,0	-
PA 425 SF 6 20 90	25	16	1"	3/4"	41,3	-
PA 425 SF 6 20 90 L 80	25	16	1"	3/4"	41,3	80


--->

PA 400 SF 6 90

Complete swage fitting 90° for HD 400

SAE flange connection, 6000 psi (SFS); material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D

L

<---


PA 425 SF 6 90	25	16	1"	1"	47,6	-
PA 425 SF 6 90 L 60	25	16	1"	1"	47,6	60
PA 425 SF 6 90 L 100	25	16	1"	1"	47,6	100
PA 425 SF 6 90 L 120	25	16	1"	1"	47,6	120
PA 425 SF 6 90 L 135	25	16	1"	1"	47,6	135
PA 425 SF 6 90 L 100	25	16	1"	1"	47,6	100
PA 425 SF 6 32 90	25	16	1"	1"1/4	54	-
PA 425 SF 6 32 90 L 100	25	16	1"	1"1/4	54	100
PA 425 SF 6 32 90 L 120	25	16	1"	1"1/4	54	120
PA 425 SF 6 32 90 L 130	25	16	1"	1"1/4	54	130
PA 425 SF 6 32 90 L 200	25	16	1"	1"1/4	54	200
PA 425 SF 6 40 90	25	16	1"	1"1/2	63,5	-

PA 500 SF 6

Complete swage fitting for HD 500

SAE flange connection, 6000 psi
(SFS), material: steel, zincd,
yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D


PA 525 SF 6	25	16	1"	1"	47,6
PA 532 SF 6 25	32	20	1"	1"	47,6
PA 532 SF 6	32	20	1"1/4	1"1/4	54
PA 532 SF 6 40	32	20	1"1/2	1"1/2	63,5
PA 540 SF 6	40	24	1"1/2	1"1/2	63,5
PA 540 SF 6 32	40	24	1"1/4	1"1/4	54
PA 540 SF 6 50	40	24	2"	2"	79,4
PA 550 SF 6	50	32	2"	2"	79,4

PA 500 SF 6 A

Complete interlock swage fitting for HD 500

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 6 A	20	12	3/4"	3/4"	41,3
PA 520 SF 6 25 A	20	12	3/4"	1"	47,6
PA 525 SF 6 20 A	20	16	1"	3/4"	41,3
PA 525 SF 6 A	25	16	1"	1"	47,6
PA 525 SF 6 32 A	25	16	1"	1"1/4	54,0
PA 532 SF 6 A	32	20	1"1/4	1"1/4	54,0
PA 532 SF 6 40 A	32	20	1"1/4	1"1/2	63,5
PA 540 SF 6 A	40	24	1"1/2	1"1/2	63,5
PA 540 SF 6 50 A	40	24	1"1/2	2"	79,4
PA 550 SF 6 A	50	32	2"	2"	79,4

PA 500 SF 6 45

Complete swage fitting 45° for HD 500

SAE flange connection, 6000 psi
(SFS), material: steel, zincd,
yellow passivated

Article category 1245




Designation	DN	size	inch	flange size (inch)	D	L
PA 525 SF 6 20 45	25	16	1"	3/4"	41,3	-
PA 525 SF 6 45	25	16	1"	1"	47,6	-
PA 525 SF 6 32 45	25	16	1"	1"1/4	54	-
PA 532 SF 6 25 45	32	20	1"	1/4"	47,6	-
PA 532 SF 6 45	32	20	1"1/4	1"1/4	54	-
PA 532 SF 6 45 L 80	32	20	1"1/4	1"1/4	54	80
PA 532 SF 6 40 45	32	20	1"1/4	1"1/2	63,5	-
PA 540 SF 6 45	40	24	1"1/2	1"1/2	63,5	-
PA 540 SF 6 50 45	40	24	1"1/2	2"	79,4	-
PA 550 SF 6 45	50	32	2"	2"	79,4	-

PA 500 SF 6 45 A

Complete interlock swage fitting 45° for HD 500

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 6 45 A	20	12	3/4"	3/4"	41,3
PA 520 SF 6 25 45 A	20	12	3/4"	1"	47,6
PA 525 SF 6 45 A	25	16	1"	1"	47,6
PA 525 SF 6 32 45 A	25	16	1"	1 1/4"	54,0
PA 532 SF 6 45 A	32	20	1 1/4"	1"	54,0
PA 532 SF 6 40 45 A	32	20	1 1/4"	1 1/2"	63,5
PA 540 SF 6 45 A	40	24	1 1/2"	1 1/2"	63,5
PA 540 SF 6 50 45 A	40	24	1 1/2"	2"	79,4
PA 550 SF 6 45 A	50	32	2"	2"	79,4

PA 500 SF 6 90

Complete swage fitting 90° for HD 500

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D

L


PA 525 SF 6 20 90	25	16	1"	3/4"	41,3	-
PA 525 SF 6 32 90	25	16	1"	1"1/4	54	-
PA 525 SF 6 90	25	16	1"	1"	47,6	-
PA 525 SF 6 90 L 100	25	16	1"	1"	47,6	100
PA 532 SF 6 25 90	32	20	1"1/4	1"	47,6	-
PA 532 SF 6 90	32	20	1"1/4	1"1/4	54	-
PA 532 SF 6 90 L 120	32	20	1"1/4	1"1/4	54	120
PA 532 SF 6 90 L 140	32	20	1"1/4	1"1/4	54	140
PA 532 SF 6 40 90	32	20	1"1/4	1"1/2	63,5	-
PA 540 SF 6 90	40	24	1"1/2	1"1/2	63,5	-
PA 540 SF 6 50 90	40	24	1"1/2	2"	79,4	-
PA 550 SF 6 90	50	32	2"	2"	79,4	-

PA 500 SF 6 90 A

Complete interlock swage fitting 90° for HD 500

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 6 25 90 A	20	12	3/4"	1"	47,6
PA 520 SF 6 90 A	20	12	3/4"	3/4"	41,3
PA 525 SF 6 20 90 A	25	16	1"	3/4"	41,3
PA 525 SF 6 90 A	25	16	1"	1"	47,6
PA 525 SF 6 32 90 A	25	16	1"	1"1/4	54,0
PA 532 SF 6 40 90 A	32	20	1"1/4	1"1/2	63,5
PA 532 SF 6 90 A	32	20	1"1/4	1"1/4	54,0
PA 540 SF 6 90 A	40	24	1"1/2	1"1/2	63,5
PA 540 SF 6 50 90 A	40	24	1"1/2	2"	79,4
PA 550 SF 6 90 A	50	32	2"	2"	79,4

PA 600 SF 6

Complete interlock swage fitting for HD 600

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D

PA 650 SF 6

50

32

2"

2"


79,4

PA 600 SF 6 45

Complete interlock swage fitting 45° for HD 600

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D

PA 650 SF 6 45

50

32

2"

2"


79,4

PA 600 SF 6 90

Complete interlock swage fitting 90° for HD 600

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D

PA 650 SF 6 90

50

32

2"

2"


79,4

PA 700 SF 6

Complete interlock swage fitting for HD 700

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245




<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>flange size (inch)</i>	<i>D</i>
PA 720 SF 6	20	12	3/4"	3/4"	41,3
PA 720 SF 6 25	20	12	3/4"	1"	47,6
PA 725 SF 6	25	16	1"	1"	47,6
PA 725 SF 6 32	25	16	1"	1"1/4	54,0
PA 732 SF 6	32	20	1"1/4	1"1/4	54,0
PA 732 SF 6 40	32	20	1"1/4	1"1/2	63,5
PA 740 SF 6	40	24	1"1/2	1"1/2	63,5
PA 740 SF 6 50	40	24	1"1/2	2"	79,4

PA 700 SF 6 45

Complete interlock swage fitting 45° for HD 700

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivate

Article category 1245




<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>flange size (inch)</i>	<i>D</i>
PA 720 SF 6 45	20	12	3/4"	3/4"	41,3
PA 720 SF 6 25 45	20	12	3/4"	1"	47,6
PA 725 SF 6 32 45	25	16	1"	1"1/4	54,0
PA 725 SF 6 45	25	16	1"	1"	47,6
PA 732 SF 6 40 45	32	20	1"1/4	1"1/2	63,5
PA 732 SF 6 45	32	20	1"1/4	1"1/4	54,0
PA 740 SF 6 45	40	24	1"1/2	1"1/2	63,5
PA 740 SF 6 50 45	40	24	1"1/2	2"	79,4

PA 700 SF 6 90

Complete interlock swage fitting 90° for HD 700

SAE flange connection, 6000 psi (SFS), material: steel, zincd, yellow passivated

Article category 1245



Designation

DN

size

inch

flange size (inch)

D


PA 720 SF 6 25 90	20	12	3/4"	1"	47,6
PA 720 SF 6 90	20	12	3/4"	3/4"	41,3
PA 725 SF 6 90	25	16	1"	1"	47,6
PA 725 SF 6 32 90	25	16	1"	1"1/4	54,0
PA 732 SF 6 90	32	20	1"1/4	1"1/4	54,0
PA 732 SF 6 40 90	32	20	1"1/4	1"1/2	63,5
PA 740 SF 6 90	40	24	1"1/2	1"1/2	63,5
PA 740 SF 6 50 90	40	24	1"1/2	2"	79,4

PA 400 SF 9

Complete swage fitting for HD 400

SAE flange connection 9000 psi,
type Caterpillar,
material: steel, zincd,
yellow passivated

Article category 1269



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>flange size (inch)</i>	<i>D</i>
--------------------	-----------	-------------	-------------	---------------------------	----------


PA 420 SF 9	20	12	3/4"	3/4"	41,3
PA 420 SF 9 25	20	12	3/4"	1"	47,6
PA 420 SF 9 32	20	12	3/4"	1"1/4	54,0
PA 425 SF 9	25	16	1"	1"	47,6
PA 425 SF 9 20	25	16	1"	3/4"	41,3
PA 425 SF 9 32	25	16	1"	1"1/4	54,0

PA 400 SF 9 45

Complete swage fitting 45°
for HD 400

SAE flange connection 9000 psi,
type Caterpillar,
material: steel, zincd,
yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 420 SF 9 25 45	20	12	3/4"	1"	47,6
PA 420 SF 9 32 45	20	12	3/4"	1"1/4	54,0
PA 420 SF 9 45	20	12	3/4"	3/4"	41,3
PA 425 SF 9 32 45	25	16	1"	1"1/4	54,0
PA 425 SF 9 45	25	16	1"	1"	47,6

PA 400 SF 9 90

Complete swage fitting 90°
for HD 400

SAE flange connection 9000 psi,
type Caterpillar,
material: steel, zincd,
yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 420 SF 9 25 90	20	12	3/4"	1"	47,6
PA 420 SF 9 90	20	12	3/4"	3/4"	41,3
PA 425 SF 9 20 90	25	16	1"	3/4"	41,3
PA 425 SF 9 32 90	25	16	1"	1"1/4	54,0
PA 425 SF 9 90	25	16	1"	1"	47,6

PA 500 SF 9

Complete swage fitting for HD 500

SAE flange connection 9000 psi,
type Caterpillar,
material: steel, zincd,
yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 532 SF 9	32	20	1"1/4	1"1/4	54,0
PA 532 SF 9 40	32	20	1"1/4	1"1/2	63,5
PA 540 SF 9	40	24	1"1/2	1"1/2	63,5

PA 500 SF 9 A

Complete interlock swage fitting for HD 500

SAE flange connection 9000 psi, type Caterpillar, material: steel, zincd, yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 9 25 A	20	12	3/4"	1"	47,6
PA 520 SF 9 A	20	12	3/4"	3/4"	41,3
PA 525 SF 9 32 A	25	16	1"	1"1/4	54,0
PA 525 SF 9 A	25	16	1"	1"	47,6
PA 532 SF 9 40 A	32	20	1"1/4	1"1/2	63,5
PA 532 SF 9 A	32	20	1"1/4	1"1/4	54,0
PA 540 SF 9 A	40	24	1"1/2	1"1/2	63,5

PA 500 SF 9 45 A

Complete interlock swage fitting 45° for HD 500

SAE flange connection 9000 psi, type Caterpillar, material: steel, zincd, yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 9 25 45 A	20	12	3/4"	1"	47,6
PA 520 SF 9 45 A	20	12	3/4"	3/4"	41,3
PA 525 SF 9 32 45 A	25	16	1"	1"1/4	54,0
PA 525 SF 9 45 A	25	16	1"	1"	47,6
PA 532 SF 9 40 45 A	32	20	1"1/4	1"1/2	63,5
PA 532 SF 9 45 A	32	20	1"1/4	1"1/4	54,0
PA 540 SF 9 45 A	40	24	1"1/2	1"1/2	63,5

PA 500 SF 9 90 A

Complete interlock swage fitting 90° for HD 500

SAE flange connection 9000 psi, type Caterpillar, material: steel, zincd, yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 520 SF 9 25 90 A	20	12	3/4"	1"	47,6
PA 520 SF 9 90 A	20	12	3/4"	3/4"	41,3
PA 525 SF 9 32 90 A	25	16	1"	1"1/4	54,0
PA 525 SF 9 90 A	25	16	1"	1"	47,6
PA 532 SF 9 40 90 A	32	20	1"1/4	1"1/2	63,5
PA 532 SF 9 90 A	32	20	1"1/4	1"1/4	54,0
PA 540 SF 9 90 A	40	24	1"1/2	1"1/2	63,5

PA 700 SF 9

Complete interlock swage fitting for HD 700

SAE flange connection 9000 psi,
type Caterpillar,
material: steel, zincd,
yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 720 SF 9	20	12	3/4"	3/4"	41,3
PA 720 SF 9 25	20	12	3/4"	1"	47,6
PA 725 SF 9	25	16	1"	1"	47,6
PA 725 SF 9 32	25	16	1"	1"1/4	54,0
PA 732 SF 9	32	20	1"1/4	1"1/4	54,0
PA 732 SF 9 40	32	20	1"1/4	1"1/2	63,5
PA 740 SF 9	40	24	1"1/2	1"1/2	63,5

PA 700 SF 9 45

Complete interlock swage fitting 45° for HD 700

SAE flange connection 9000 psi, type Caterpillar, material: steel, zined, yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 720 SF 9 25 45	20	12	3/4"	1"	47,6
PA 720 SF 9 45	20	12	3/4"	3/4"	41,3
PA 725 SF 9 32 45	25	16	1"	1"1/4	54,0
PA 725 SF 9 45	25	16	1"	1"	47,6
PA 732 SF 9 40 45	32	20	1"1/4	1"1/2	63,5
PA 732 SF 9 45	32	20	1"1/4	1"1/4	54,0
PA 740 SF 9 45	40	24	1"1/2	1"1/2	63,5

PA 700 SF 9 90

Complete interlock swage fitting 90° for HD 700

SAE flange connection 9000 psi, type Caterpillar, material: steel, zincd, yellow passivated

Article category 1269



Designation

DN

size

inch

flange size (inch)

D


PA 720 SF 9 25 90	20	12	3/4"	1"	47,6
PA 720 SF 9 90	20	12	3/4"	3/4"	41,3
PA 725 SF 9 90	25	16	1"	1"	47,6
PA 725 SF 9 32 90	25	16	1"	1"1/4	54,0
PA 732 SF 9 40 90	32	20	1"1/4	1"1/2	63,5
PA 732 SF 9 90	32	20	1"1/4	1"1/4	54,0
PA 740 SF 9 90	40	24	1"1/2	1"1/2	63,5

PA 400 FT

Complete swage fitting for HD 400

with O-ring, metric union nut,
Hanomag,
material: steel, zincd,
yellow passivated

Article category 1251



Designation

DN

size

inch

thread

PA 420 FT

20

12

3/4"

M 35x3

PA 425 FT

25

16

1"

M 45x3

PA 400 AJF

Complete swage fitting for HD 400

UNF thread, flat seat, ORFS
female fitting, material: steel,
zincd, yellow passivated

Article category 1253



Designation

DN

size

inch

thread

T

SW


PA 406 AJF	6	4	1/4"	9/16"-18	13	19
PA 410 AJF	10	6	3/8"	11/16"-16	15,9	22
PA 413 AJF	13	8	1/2"	13/16"-16	19,1	24
PA 416 AJF	16	10	5/8"	1"-14	23,7	30
PA 420 AJF	20	12	3/4"	1"3/16-12	28,0	36
PA 425 AJF	25	16	1"	1"7/16-12	34,4	41

PA 400 AJF 45

Complete swage fitting 45°
for HD 400

UNF thread, flat seat, ORFS
female fitting, material: steel,
zincd, yellow passivated

Article category 1253




<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>T</i>	<i>SW</i>
PA 406 AJF 45	6	4	1/4"	9/16"-18	13	19
PA 410 AJF 45	10	6	3/8"	11/16"-16	15,9	22
PA 413 AJF 45	13	8	1/2"	13/16"-16	19,1	24
PA 416 AJF 45	16	10	5/8"	1"-14	23,7	30
PA 420 AJF 45	20	12	3/4"	1"3/16-12	28,0	36
PA 425 AJF 45	25	16	1"	1"7/16-12	34,5	41

PA 400 AJF 90

Complete swage fitting 90° for HD 400

UNF thread, flat seat, for ORFS
connection, material: steel,
zincd, yellow passivated

Article category 1253



Designation

DN

size

inch

thread

T

SW


PA 406 AJF 90	6	4	1/4"	9/16"-18	13	19
PA 410 AJF 90	10	6	3/8"	11/16"-16	15,9	22
PA 413 AJF 90	13	8	1/2"	13/16"-16	19,1	24
PA 416 AJF 90	16	10	5/8"	1"-14	23,7	30
PA 420 AJF 90	20	12	3/4"	1"3/16-12	28,0	36
PA 425 AJF 90	25	16	1"	17/16"-12	34,5	41
PA 425 AJF 90 L 114	25	16	1"	17/16"-12	34,5	41

PA 400 SO

Complete swage fitting for HD 400

O-connection, O-ring sealing for
connecting sleeve,
material: steel, zincd,
yellow passivated

Article category 1282



Designation

DN

size

inch

O-ring

backup ring


PA 410 SO	10	6	3/8"	6x2	10,1x6,8-0,8
PA 413 SO	13	8	1/2"	10x2	14,1x10,8-0,8
PA 420 SO	20	12	3/4"	16x2,1	21,1x17-0,8
PA 425 SO	25	16	1"	19x2,5	24,1x20x0,8

PA 500 S0

Complete swage fitting for HD 500

O-ring sealing for connecting
sleeve, material: steel, zincd,
yellow passivated

Article category 1282



Designation

DN

size

inch

O-ring

backup ring

PA 532 S0

32

20

1"1/4

33x2,5


38,1-34,0

PA 400 SFK

Complete swage fitting for HD 400

SAE flange, type Komatsu,
material: steel, zincd,
yellow passivated

Article category 1283



Designation

DN

size

inch

D

PA 413 SFK

13

8

1/2"

34

PA 416 SFK

16

10

5/8"


34

PA 400 SFK 45

Complete swage fitting 45°
for HD 400

SAE flange, type Komatsu,
material: steel, zincd,
yellow passivated

Article category 1283



Designation

DN

size

inch

D

PA 413 SFK 45

13

8

1/2"

34

PA 416 SFK 45

16

10

5/8"


34

PA 400 SFK 90

Complete swage fitting 90°
for HD 400,

SAE flange, type Komatsu,
material: steel, zincd,
yellow passivated

Article category 1283



Designation

DN

size

inch

D

PA 413 SFK 90

13

8

1/2"

34

PA 416 SFK 90

16

10

5/8"


34

PA 400 AB

Complete swage fitting for HD 400

BSP female fitting with 60° cone
(DKR), material: steel, zincd,
yellow passivated

Article category 1287




Designation	DN	size	inch	thread	ID	SW
PA 406 AB	6	4	1/4"	1/4"	11,5	19
PA 410 AB	10	6	3/8"	3/8"	14,9	22
PA 413 AB	13	8	1/2"	1/2"	18,6	27
PA 416 AB	16	10	5/8"	5/8"	20,6	28
PA 416 AB 13	16	10	5/8"	1/2"	18,6	27
PA 416 AB 20	16	10	5/8"	3/4"	24,1	32
PA 420 AB	32	12	3/4"	3/4"	24,1	32
PA 420 AB 25	20	12	3/4"	1"	30,3	41
PA 425 AB	25	16	1"	1"	30,3	41
PA 425 AB 32	25	16	1"	1"1/4	38,9	50

PA 400 AB 45

Complete swage fitting 45° for HD 400

union BSP nut, 60° cone (DKR),
material: steel, zincd,
yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D

SW


PA 410 AB 45	10	6	3/8"	3/8"	14,9	22
PA 413 AB 45	13	8	1/2"	1/2"	18,6	27
PA 416 AB 45	16	10	5/8"	5/8"	20,6	28
PA 420 AB 45	20	12	3/4"	3/4"	24,1	32
PA 420 AB 2545	20	12	3/4"	1"	30,3	41
PA 425 AB 3245	25	16	1"	1"1/4	38,9	50
PA 425 AB 45	25	16	1"	1"	30,3	41

PA 400 AB 90

Complete swage fitting 90° for HD 400

union BSP nut, 60° cone (DKR),
material: steel, zincd,
yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D


SW

PA 410 AB 90	10	6	3/8"	3/8"	14,9	22
PA 413 AB 90	13	8	1/2"	1/2"	18,6	27
PA 416 AB 90	16	10	5/8"	5/8"	20,6	28
PA 416 AB 20 90	16	10	5/8"	3/4"	24,1	32
PA 420 AB 90	20	12	3/4"	3/4"	24,1	32
PA 425 AB 3290	25	16	1"	1"1/4	38,9	50
PA 425 AB 90	25	16	1"	1"	30,3	41

PA 500 AB

Complete swage fitting for HD 500

union BSP nut, 60° cone (DKR),
material: steel, zincd,
yellow passivated
Article category 1287



Designation

DN

size

inch

thread

D

A

PA 532 AB

32

20

1"1/4

1"1/4

38,9

50

PA 540 AB

40

24

1"1/2

1"1/2

44,9

55

PA 550 AB

50

32

2"

2"

56,7


70

PA 500 AB A

Complete interlock swage fitting for HD 500

with BSP union nut, 60° cone (DKR), material: steel, zincd, yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D

SW


PA 520 AB A	20	12	3/4"	3/4"	24,1	32
PA 525 AB A	25	16	1"	1"	30,3	41
PA 532 AB A	32	20	1"1/4	1"1/4	38,9	50
PA 540 AB A	40	24	1"1/2	1"1/2	44,9	55
PA 550 AB A	50	32	2"	2"	56,7	70

PA 500 AB 45

Complete swage fitting 45° for HD 500

with union BSP nut and 60° cone
(DKR), material: steel, zincd,
yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D

SW


PA 532 AB 45	32	20	1"1/4	1"1/4	38,9	50
PA 540 AB 45	38	24	1"1/2	1"1/2	44,9	55
PA 550 AB 45	50	32	2"	2"	56,7	70

PA 500 AB 45 A

Complete interlock swage fitting 45° for HD 500

with BSP union nut, 60° cone (DKR), material: steel, zincd, yellow passivated

Article category 1287



<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>D</i>	<i>SW</i>
--------------------	-----------	-------------	-------------	---------------	----------	-----------


PA 520 AB 45 A	20	12	3/4"	3/4	24,1	32
PA 525 AB 45 A	25	16	1"	1"	30,3	41
PA 532 AB 45 A	32	20	1"1/4	1"1/4	38,9	50
PA 540 AB 45 A	40	24	1"1/2	1"1/2	44,9	55
PA 550 AB 45 A	50	32	2"	2"	56,7	70

PA 500 AB 90

Complete swage fitting 90° for HD 500

with BSP nut and 60° cone
(DKR), material: steel, zincd,
yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D

SW

PA 532 AB 90

32

20

1"1/4

1"1/4

38,9

50

PA 540 AB 90

40

24

1"1/2

1"1/2

44,9

55

PA 550 AB 90

50

32

2"

2"

56,7


70

PA 500 AB 90 A

Complete interlock swage fitting 90° for HD 500

union BSP nut, 60° cone (DKR),
material: steel, zincd,
yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D

SW


PA 520 AB 90 A	20	12	3/4"	3/4"	24,1	32
PA 525 AB 90 A	25	16	1"	1"	30,3	41
PA 532 AB 90 A	32	20	1"1/4	1"1/4	38,9	50
PA 540 AB 90 A	40	24	1"1/2	1"1/2	44,9	55
PA 550 AB 90 A	50	32	2"	2"	56,7	70

PA 700 AB

Complete interlock swage fitting for HD 700

with 60° cone (DKR) and union BSP nut, material: steel, zincd, yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D

SW


PA 720 AB	20	12	3/4"	3/4"	24,1	32
PA 725 AB	25	16	1"	1"	30,3	41
PA 732 AB	32	20	1"1/4	1"1/4	38,9	50
PA 740 AB	40	24	1"1/2	1"1/2	44,9	55

PA 700 AB 45

Complete interlock swage fitting 45° for HD 700

with 60° cone (DKR) and union BSP nut, material: steel, zincd, yellow passivated

Article category 1287




<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>D</i>	<i>SW</i>
PA 720 AB 45	20	12	3/4"	3/4"	24,1	32
PA 725 AB 45	25	16	1"	1"	30,3	41
PA 732 AB 45	32	20	1"1/4	1"1/4	38,9	50
PA 740 AB 45	40	24	1"1/2	1"1/2	44,9	55

PA 700 AB 90

Complete interlock swage fitting 90° for HD 700

with 60° cone (DKR) and union BSP nut, material: steel, zincd, yellow passivated

Article category 1287



Designation

DN

size

inch

thread

D

SW


PA 720 AB 90	20	12	3/4"	3/4"	24,1	32
PA 725 AB 90	25	16	1"	1"	30,3	41
PA 732 AB 90	32	20	1"1/4	1"1/4	38,9	50
PA 740 AB 90	40	24	1"1/2	1"1/2	44,9	55

PA 500 AOB A

Complete interlock swage fitting for HD 500

O-ring, union nut, BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288



Designation

DN

size

inch

thread

D

SW


PA 520 AOB A	20	12	3/4"	3/4"	24,1	32
PA 525 AOB A	25	16	1"	1"	30,3	41
PA 532 AOB A	32	20	1"1/4	1"1/4	38,9	50
PA 540 AOB A	40	24	1"1/2	1"1/2	44,9	55
PA 550 AOB A	50	32	2"	2"	56,7	70

PA 500 AOB 45 A

Complete interlock swage fitting 45° for HD 500

O-ring, union nut, BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288



Designation

DN

size

inch

thread

D

SW


PA 520 AOB 45 A	20	12	3/4"	3/4"	24,1	32
PA 525 AOB 45 A	25	16	1"	1"	30,3	41
PA 532 AOB 45 A	32	20	1"1/4	1"1/4	38,9	50
PA 540 AOB 45 A	40	24	1"1/2	1"1/2	44,9	55
PA 550 AOB 45 A	50	32	2"	2"	56,7	70

PA 500 AOB 90 A

Complete interlock swage fitting 90° for HD 500

O-ring, union nut, BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288




<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>D</i>	<i>SW</i>
PA 520 AOB 90 A	20	12	3/4"	3/4"	24,1	32
PA 525 AOB 90 A	25	16	1"	1"	30,3	41
PA 532 AOB 90 A	32	20	1"1/4	1"1/4	38,9	50
PA 540 AOB 90 A	40	24	1"1/2	1"1/2	44,9	55
PA 550 AOB 90 A	50	32	2"	2"	56,7	70

PA 600 AOB

Complete interlock swage fitting for HD 600

O-ring seal, union nut, BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288



Designation

DN

size

inch

thread

D

SW

PA 650 AOB

50

32

2"

2"

56,7


70

PA 600 AOB 45

Complete interlock swage fitting 45° for HD 600

O-ring seal, union nut, BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288



Designation

DN

size

inch

thread

D

SW

PA 650 AOB 45

50

32

2"

2"

56,7


70

PA 600 AOB 90

Complete interlock swage fitting 90° for HD 500

O-ring seal, union nut, BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288



Designation

DN

size

inch

thread

A

B

PA 650 AOB 90

50

32

2"

2"

56,7


70

PA 700 AOB

Complete interlock swage fitting for HD 700

O-ring seal, union nut and BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288



Designation

DN

size

inch

thread

D

SW


PA 720 AOB	20	12	3/4"	3/4"	24,1	32
PA 725 AOB	25	16	1"	1"	30,3	41
PA 732 AOB	32	20	1"1/4	1"1/4	38,9	50
PA 740 AOB	40	24	1"1/2	1"1/2	44,9	55

PA 700 AOB 45

Complete interlock swage fitting 45° for HD 700

O-ring seal, union nut and BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288




<i>Designation</i>	<i>DN</i>	<i>size</i>	<i>inch</i>	<i>thread</i>	<i>D</i>	<i>SW</i>
PA 720 AOB 45	20	12	3/4"	3/4"	24,1	32
PA 725 AOB 45	25	16	1"	1"	30,3	41
PA 732 AOB 45	32	20	1"1/4	1"1/4	38,9	50
PA 740 AOB 45	40	24	1"1/2	1"1/2	44,9	55

PA 700 AOB 90

Complete interlock swage fitting 90° for HD 700

O-ring seal, union nut and BSP thread, 60° cone (DKOR), material: steel, zincd, yellow passivated

Article category 1288



Designation

DN

size

inch

thread

D

SW


PA 720 AOB 90	20	12	3/4"	3/4"	24,1	32
PA 725 AOB 90	25	16	1"	1"	30,3	41
PA 732 AOB 90	32	20	1"1/4	1"1/4	38,9	50
PA 740 AOB 90	40	24	1"1/2	1"1/2	44,5	55

PA 400 AR

Complete swage fitting for HD 400

union BSP nut, flat seat,
material: steel, zined,
yellow passivated

Article category 1291



Designation	DN	size	inch	thread	D	SW
-------------	----	------	------	--------	---	----


PA 413 AR	13	8	1/2"	1/2"	18,6	27
PA 420 AR	20	12	3/4"	3/4"	24,1	32

PA 400 HB

Complete swage fitting for HD 400

male BSP thread, 60° cone seat
(AGR), material: steel, zincd,
yellow passivated

Article category 1294



Designation

DN

size

inch

thread

D


PA 406 HB	6	4	1/4"	1/4"	13,16
PA 410 HB	10	6	3/8"	3/8"	16,66
PA 413 HB	13	8	1/2"	1/2"	20,96
PA 416 HB	16	10	5/8"	5/8"	22,91
PA 420 HB	20	12	3/4"	3/4"	26,44
PA 420 HB 25	20	12	3/4"	1"	33,25
PA 425 HB	25	16	1"	1"	33,25

PA 500 HB

Complete swage fitting for HD 500

male BSP thread (AGR),
60° cone seat (AGR),
material: steel, zincd,
yellow passivated

Article category 1294



Designation

DN

size

inch

thread

D


PA 532 HB	32	20	1"1/4	1"1/4	41,91
PA 540 HB	40	24	1"1/2	1"1/2	47,80
PA 550 HB	50	32	2"	2"	59,62

PA 500 HB A

Complete interlock swage fitting for HD 500

male BSP thread (AGR),
60° cone seat (AGR),
material: steel, zincd,
yellow passivated

Article category 1294



Designation

DN

size

inch

thread

D


PA 520 HB A	20	12	3/4"	3/4"	26,44
PA 525 HB A	25	16	1"	1"	33,25
PA 532 HB A	32	20	1"1/4	1"1/4	41,91
PA 540 HB A	40	24	1"1/2	1"1/2	47,80
PA 550 HB A	50	32	2"	2"	59,62

PA 600 HB

Complete interlock swage fitting for HD 600

with male BSP thread and
60° cone seat (AGR),
material: steel, zincd,
yellow passivated

Article category 1294



Designation

DN

size

inch

thread

A

PA 650 HB

50

32

2"

2"


59,62

PA 700 HB

Complete interlock swage fitting for HD 700

with male BSP thread and 60° cone seat (AGR), material: steel, zincd, yellow passivated

Article category 1294



Designation

DN

size

inch

thread

D

PA 720 HB	20	12	3/4"	3/4"	26,44
PA 725 HB	25	16	1"	1"	33,25
PA 732 HB	32	20	1"1/4	1"1/4	41,91
PA 740 HB	40	24	1"1/2	1"1/2	47,80

PA 500 HBK A

Complete interlock swage fitting for HD 500

male BSPT taper seal,
material: steel, zincd,
yellow passivated

Article category 1294



Designation

DN

size

inch

thread

PA 520 HBK A	20	12	3/4"	3/4"-14
PA 525 HBK A	25	16	1"	1"-11
PA 532 HBK A	32	20	1"1/4	1"1/4-11
PA 540 HBK A	40	24	1"1/2	1"1/2-11
PA 550 HBK A	50	32	2"	2"-11

PA 600 HBK

Complete interlock swage fitting for HD 600

male BSPT taper seal,
material: steel, zincd,
yellow passivated

Article category 1294



Designation

DN

size

inch

thread

PA 650 HBK

50

32

2"

2"-11

PA 700 HBK

Complete interlock swage fitting for HD 700

male BSPT taper seal,
material: steel, zincd,
yellow passivated

Article category 1294



Designation

DN

size

inch

thread

PA 720 HBK	20	12	3/4"	3/4"-14
PA 725 HBK	25	16	1"	1"-11
PA 732 HBK	32	20	1"1/4	1"1/4-11
PA 740 HBK	40	24	1"1/2	1"1/2-11

PA 700 VB

Complete interlock swage
fitting connection for HD 700

double connection,
material: steel, zincd,
yellow passivated

Article category 1297



Designation

DN

size

inch

PA 720 VB	20	12	3/4"
PA 725 VB	25	16	1"
PA 732 VB	32	20	1"1/4
PA 740 VB	40	24	1"1/2

PA 500 VB A

Complete interlock swage
fitting connection for HD 500

double connection,
material: steel, zincd,
yellow passivated

Article category 1297



Designation

DN

size

inch

PA 520 VB A	20	12	3/4"
PA 525 VB A	25	16	1"
PA 532 VB A	32	20	1"1/4
PA 540 VB A	40	24	1"1/2
PA 550 VB A	50	32	2"

Index

C

Complete interlock swage fitting 45° for HD 500	21
Complete interlock swage fitting 45° for HD 500	27
Complete interlock swage fitting 45° for HD 500	57
Complete interlock swage fitting 45° for HD 500	64
Complete interlock swage fitting 45° for HD 500	85
Complete interlock swage fitting 45° for HD 500	101
Complete interlock swage fitting 45° for HD 500	115
Complete interlock swage fitting 45° for HD 500	135
Complete interlock swage fitting 45° for HD 500	142
Complete interlock swage fitting 45° for HD 600	105
Complete interlock swage fitting 45° for HD 600	145
Complete interlock swage fitting 45° for HD 700	24
Complete interlock swage fitting 45° for HD 700	61
Complete interlock swage fitting 45° for HD 700	67

Complete interlock swage fitting 45° for HD 700	108
Complete interlock swage fitting 45° for HD 700	118
Complete interlock swage fitting 45° for HD 700	139
Complete interlock swage fitting 45° for HD 700	148
Complete interlock swage fitting 90° for HD 500	22
Complete interlock swage fitting 90° for HD 500	28
Complete interlock swage fitting 90° for HD 500	59
Complete interlock swage fitting 90° for HD 500	65
Complete interlock swage fitting 90° for HD 500	87
Complete interlock swage fitting 90° for HD 500	103
Complete interlock swage fitting 90° for HD 500	116
Complete interlock swage fitting 90° for HD 500	137
Complete interlock swage fitting 90° for HD 500	143
Complete interlock swage fitting 90° for HD 500	146
Complete interlock swage fitting 90° for HD 600	106

Index

Complete interlock swage fitting 90° for HD 700	25	Complete interlock swage fitting for HD 500	63
Complete interlock swage fitting 90° for HD 700	62	Complete interlock swage fitting for HD 500	71
Complete interlock swage fitting 90° for HD 700	68	Complete interlock swage fitting for HD 500	76
Complete interlock swage fitting 90° for HD 700	109	Complete interlock swage fitting for HD 500	83
Complete interlock swage fitting 90° for HD 700	119	Complete interlock swage fitting for HD 500	99
Complete interlock swage fitting 90° for HD 700	140	Complete interlock swage fitting for HD 500	114
Complete interlock swage fitting 90° for HD 700	149	Complete interlock swage fitting for HD 500	133
Complete interlock swage fitting connection for HD 500	160	Complete interlock swage fitting for HD 500	141
Complete interlock swage fitting connection for HD 700	159	Complete interlock swage fitting for HD 500	153
Complete interlock swage fitting for HD 400	17	Complete interlock swage fitting for HD 500	156
Complete interlock swage fitting for HD 500	20	Complete interlock swage fitting for HD 600	77
Complete interlock swage fitting for HD 500	26	Complete interlock swage fitting for HD 600	88
Complete interlock swage fitting for HD 500	29	Complete interlock swage fitting for HD 600	104
Complete interlock swage fitting for HD 500	37	Complete interlock swage fitting for HD 600	144
Complete interlock swage fitting for HD 500	55	Complete interlock swage fitting for HD 600	154

Index

Complete interlock swage fitting for HD 600	157	Complete swage fitting 45° for HD 400	8
Complete interlock swage fitting for HD 700	23	Complete swage fitting 45° for HD 400	18
Complete interlock swage fitting for HD 700	36	Complete swage fitting 45° for HD 400	33
Complete interlock swage fitting for HD 700	60	Complete swage fitting 45° for HD 400	52
Complete interlock swage fitting for HD 700	66	Complete swage fitting 45° for HD 400	80
Complete interlock swage fitting for HD 700	73	Complete swage fitting 45° for HD 400	95
Complete interlock swage fitting for HD 700	78	Complete swage fitting 45° for HD 400	111
Complete interlock swage fitting for HD 700	91	Complete swage fitting 45° for HD 400	122
Complete interlock swage fitting for HD 700	107	Complete swage fitting 45° for HD 400	127
Complete interlock swage fitting for HD 700	117	Complete swage fitting 45° for HD 400	130
Complete interlock swage fitting for HD 700	138	Complete swage fitting 45° for HD 500	5
Complete interlock swage fitting for HD 700	147	Complete swage fitting 45° for HD 500	9
Complete interlock swage fitting for HD 700	155	Complete swage fitting 45° for HD 500	56
Complete interlock swage fitting for HD 700	158	Complete swage fitting 45° for HD 500	84
Complete swage fitting 45° for HD 400	2	Complete swage fitting 45° for HD 500	100

Index

Complete swage fitting 45° for HD 500	134	Complete swage fitting 90° for HD 500	11
Complete swage fitting 45° for HD 600	89	Complete swage fitting 90° for HD 500	58
Complete swage fitting 45° for HD 700	92	Complete swage fitting 90° for HD 500	86
Complete swage fitting 45° French series	40	Complete swage fitting 90° for HD 500	136
Complete swage fitting 90° for HD 400	3	Complete swage fitting 90° for HD 600	90
Complete swage fitting 90° for HD 400	10	Complete swage fitting 90° for HD 700	93
Complete swage fitting 90° for HD 400	19	Complete swage fitting 90° for HD 400	53
Complete swage fitting 90° for HD 400	34	Complete swage fitting 90°, French series for HD 400	41
Complete swage fitting 90° for HD 400	81	Complete swage fitting for HD 400	1
Complete swage fitting 90° for HD 400	96-97	Complete swage fitting for HD 400	6
Complete swage fitting 90° for HD 500	102	Complete swage fitting for HD 400	12-13
Complete swage fitting 90° for HD 400	112	Complete swage fitting for HD 400	15-16
Complete swage fitting 90° for HD 400	123	Complete swage fitting for HD 400	30-32
Complete swage fitting 90° for HD 400	128	Complete swage fitting for HD 400	42
Complete swage fitting 90° for HD 400	131	Complete swage fitting for HD 400	44-46
		Complete swage fitting for HD 400	49-51
		Complete swage fitting for HD 400	69

Index

Complete swage fitting for HD 400	74
Complete swage fitting for HD 400	79
Complete swage fitting for HD 400	94
Complete swage fitting for HD 400	110
Complete swage fitting for HD 400	120-121
Complete swage fitting for HD 400	124
Complete swage fitting for HD 400	126
Complete swage fitting for HD 400	129
Complete swage fitting for HD 400	150-151
Complete swage fitting for HD 500	4
Complete swage fitting for HD 500	7
Complete swage fitting for HD 500	14
Complete swage fitting for HD 500	35
Complete swage fitting for HD 500	43
Complete swage fitting for HD 500	47-48
Complete swage fitting for HD 500	54
Complete swage fitting for HD 500	70
Complete swage fitting for HD 500	75
Complete swage fitting for HD 500	82
Complete swage fitting for HD 500	98
Complete swage fitting for HD 500	113
Complete swage fitting for HD 500	125
Complete swage fitting for HD 500	132
Complete swage fitting for HD 500	152
Complete swage fitting for HD 600	72

Complete swage fitting, French series	39
---------------------------------------	----

P

PA 400 A 45	8
PA 400 A 90	10
PA 400 A	6
PA 400 AB 45	130
PA 400 AB 90	131
PA 400 AB	129
PA 400 AF 45	40
PA 400 AF 90	41
PA 400 AF	39
PA 400 AFS	15
PA 400 AJ 45	52
PA 400 AJ 90	53
PA 400 AJ	51
PA 400 AJF 45	122
PA 400 AJF 90	123
PA 400 AJF	121
PA 400 ALI	12
PA 400 AOL 45	2
PA 400 AOL 90	3
PA 400 AOL	1
PA 400 AOS 45	18
PA 400 AOS 90	19
PA 400 AOS A	17
PA 400 AOS	16

Index

PA 400 AR	150	PA 400 SPL 90	46
PA 400 FL	13	PA 400 SPL 90Q	50
PA 400 FS	30	PA 400 SPL Q	49
PA 400 FT	120	PA 400 SPL	45
PA 400 HB	151	PA 500 A 45	9
PA 400 HF	38	PA 500 A 90	11
PA 400 HJ	69	PA 500 A	7
PA 400 HL	31	PA 500 AB 45 A	135
PA 400 HN	74	PA 500 AB 45	134
PA 400 HS 45	33	PA 500 AB 90 A	137
PA 400 HS 90	34	PA 500 AB 90	136
PA 400 HS	32	PA 500 AB A	133
PA 400 SF 45	80	PA 500 AB	132
PA 400 SF 6 45	95	PA 500 AJ 45 A	57
PA 400 SF 6 90	96-97	PA 500 AJ 45	56
PA 400 SF 6	94	PA 500 AJ 90 A	59
PA 400 SF 9 45	111	PA 500 AJ 90	58
PA 400 SF 9 90	112	PA 500 AJ A	55
PA 400 SF 9	110	PA 500 AJ	54
PA 400 SF 90	81	PA 500 AOB 45 A	142
PA 400 SF	79	PA 500 AOB 90 A	143
PA 400 SFK 45	127	PA 500 AOB A	141
PA 400 SFK 90	128	PA 500 A0J 45 A	64
PA 400 SFK	126	PA 500 A0J 90 A	65
PA 400 S0	124	PA 500 A0J A	63
PA 400 SPF Q	44	PA 500 AOL 45	5
PA 400 SPF	42	PA 500 AOL	4

Index

PA 500 AOS 45 A	21	PA 500 SF 9 A	114
PA 500 AOS 90A	22	PA 500 SF 9	113
PA 500 AOS A H	29	PA 500 SF 90 A	87
PA 500 AOS A	20	PA 500 SF 90	86
PA 500 AOSS 45 A	27	PA 500 SF A	83
PA 500 AOSS 90 A	28	PA 500 SF	82
PA 500 AOSS A	26	PA 500 SO	125
PA 500 FL	14	PA 500 SPF	43
PA 500 HB A	153	PA 500 SPL 90	48
PA 500 HB	152	PA 500 SPL	47
PA 500 HBK A	156	PA 500 VB A	160
PA 500 HJ A	71	PA 600 AOB 45	145
PA 500 HJ	70	PA 600 AOB 90	146
PA 500 HN A	76	PA 600 AOB	144
PA 500 HN	75	PA 600 HB	154
PA 500 HS A	37	PA 600 HBK	157
PA 500 HS	35	PA 600 HJ	72
PA 500 SF 45 A	85	PA 600 HN	77
PA 500 SF 45	84	PA 600 SF 45	89
PA 500 SF 6 45 A	101	PA 600 SF 6 45	105
PA 500 SF 6 45	100	PA 600 SF 6 90	106
PA 500 SF 6 90 A	103	PA 600 SF 6	104
PA 500 SF 6 90	102	PA 600 SF 90	90
PA 500 SF 6 A	99	PA 600 SF	88
PA 500 SF 6	98	PA 700 AB 45	139
PA 500 SF 9 45 A	115	PA 700 AB 90	140
PA 500 SF 9 90 A	116	PA 700 AB	138

Index

PA 700 AJ 45	61
PA 700 AJ 90	62
PA 700 AJ	60
PA 700 AOB 45	148
PA 700 AOB 90	149
PA 700 AOB	147
PA 700 AOJ 45	67
PA 700 AOJ 90	68
PA 700 AOJ	66
PA 700 AOS 45	24
PA 700 AOS 90	25
PA 700 AOS	23
PA 700 HB	155
PA 700 HBK	158
PA 700 HJ	73
PA 700 HN	78
PA 700 HS	36
PA 700 SF 45	92
PA 700 SF 6 45	108
PA 700 SF 6 90	109
PA 700 SF 6	107
PA 700 SF 9 45	118
PA 700 SF 9 90	119
PA 700 SF 9	117
PA 700 SF 90	93
PA 700 SF	91
PA 700 VB	159

S

Swage fitting, French series	38
------------------------------	----