



Good planning and equipment selection is the key to good performance with the resulting improvement in standards of both cleanliness and hygiene.

Careful consideration of each and every area to be cleaned, the frequency necessary and the staff availability is essential and by ensuring the correct equipment selection to meet your criteria, efficiency will be seen to increase and the quality of the results will visibly improve.



Numatic International Limited, Chard, Somerset, TA20 2GB
Tel: +44 (0)1460 68600 Fax: +44 (0)1460 68458
www.numatic.co.uk © Numatic International Limited 2006 233556/04061A

LoLine
332
&
415

Twintec
345
&
665

Twintec
3450
&
6652



New LoLines... you asked for them..

The LoLine range of low profile floorcare machines has been developed to meet both the growing demand and need for a choice of models that are smaller in size, lighter in weight, compact and convenient in storage whilst, at the same time, being quick and easy to use without loss of performance.


The new LoLine rotaries have been designed specifically to meet this demand and raises the handling and performance levels to an exceptional user friendly standard be it for men or women operators.

LoLine 332 (33cm/200rpm)

The smallest model in the LoLine range can claim performance characteristics equal to that of bigger, more industrial machines, yet with an ease and speed of operation that will immediately endear it to any operator.

A full range of 33cm (13") brushes and pad drives allows the machine to be used for all of the primary floorcare functions. With a total weight of only 18Kg and an operating speed of 200rpm the machine literally exudes convenience and versatility. Fast and user friendly like never before.

Motor	Deck	Brush	Pad	Power	Speed	Range	Weight	Size
400W	330mm	330mm	330mm	230V AC 50Hz	200rpm	32m	18Kgs	1145 x 330 x 540mm




LoLine 415 (40cm/150rpm)

The LoLine 415 model embodies all of the many unique features of the 332 but is suitable for a range of larger 40cm (16") brushes and 36cm (14") floor pads.

With this machine running at an operating speed of 150rpm it is a genuine taskmaster, satisfying a whole host of floor maintenance needs, be it polishing, scrubbing or rotary carpet cleaning, and yet with an ease of handling that cannot fail to impress any user, and even more so where extended operating hours are part of the daily routine.

The solution tank system allows for easy use and compact storage, whilst its unique universal filling system adds further to operator convenience.

Motor	Deck	Brush	Pad	Power	Speed	Range	Weight	Size
400W	400mm	400mm	360mm	230V AC 50Hz	150rpm	32m	18.5Kgs	1145 x 360 x 540mm



LoLine as it's name suggests, has an exceptionally 'low' profile, as low as 19cm (7.5").

19cm



...now you have them!

NLL415

New Twintecs!

Twintec 6652 TRACTION

The use and application of semi-automatic scrubber dryers has grown in leaps and bounds over the past 10 years but, at the same time, the extended use and needs of these machines has demanded an increase in model selection to reflect the changing requirements of the professional user.

The new Twintec models reflect developments at both ends of the scale and will be joined in early 2007 by further innovation and complimentary designs.




Twintec TTB6652T Traction

The new 6652 traction machine is truly a careful balance of existing design criteria and a wealth of new and improved technology, all designed to produce handling and operational standards second to none.

The low level, stainless steel chassis provides a sound foundation for the full 200Ahr 24V power supply with its own fully integrated charging system. This is complimented throughout by a powerful series of drive and suction motors providing up to 3.5 hrs of robust operation from a single 8 hour charge.

With the user in full control of the operating speeds in both forward and reverse directions, the machine can be individually programmed to suit a whole range of environments to ensure optimum results.

Model	Brush Motor	Vac Motor	Power	Time	Traction Drive	Scrub Width	Brush Speed	Capacity	Weight	Size
TTB6652T	2 x 24V 400W	24V 400W	4 x 12V (24V) ≈ 200Ahr	3.50hrs	250W	650mm 2 x 330mm	200rpm	60L	240Kg	1430 x 1200 x 970mm



Twintec 3450 Cylinder

Twintec TT/TTBB3450C

The popular 3450 model with its 30 litre capacity and 45cm (18") scrubbing width now arrives as a cylinder version, available in both cable and battery models.

The cylinder power brush design provides truly deep cleaning performance, whilst the twin wet pick-up nozzles either side of the brush roll, permit multidirectional operation (forward and backwards) which is vitally important when cleaning the narrow aisles and walkways often found in shops and food stores.

With the cylinder model you can walk in forwards and walk out backwards without the need for turning and without loss of scrubbing and drying performance.

With generous capacity and 2.25 hour operational performance, the 3450 cylinder will satisfy many applications within the retail and other environments suffering from restricted movement space.

Model	Brush Motor	Vac Motor	Power	Scrub Width	Speed	Capacity	Range	Weight	Size
TT3450C	1000W	1200W	230V A6 50Hz	450mm	50Hz=150rpm 60Hz=180rpm	30L	42m	57Kg	1280 x 1150 x 590mm

Model	Brush Motor	Vac Motor	Power	Time	Scrub Width	Speed	Capacity	Weight	Size
TTB3450C	24V 400W	24V 400W	2 x 12V (24V) 100Ahr	2.25hrs	450mm	120rpm	30L	122Kg	1280 x 1150 x 590mm

