

4 LOAD CELL STAINLESS STEEL SCALE



Measurement with application of 4 load cells is a guarantee of precise readout, no matter of place of loading the mass on the weighing pan.



Counting pieces



Checkweighing



Summing function

This platform scales with 4 load cells are manufactured in fully stainless steel technology and are also offered in pit version= equipped with openable weighing platform (for easy cleaning area under the platform).

Stainless steel measuring indicator PUE C/31H with backlit LCD display is installed on 3 meter long cable with possibility of mounting on wall. Range of capacities for this scale varies from 300 kg / 100 g up to 6000 kg / 2000g.

Scales are powered from mains, RS 232 output is offered as standard.

Technical data:

	WPT/4 300H6	WPT/4 600H6	WPT/4 300H7	WPT/4 600H7	WPT/4 1500H7
Max capacity	300 kg	600 kg	300 kg	600 kg	1500 kg
Readability	100 g	200 g	100 g	200 g	500 g
Tare range	-300 kg	-600 kg	-300 kg	-600 kg	-1500 kg
Pan size	800×800 mm	800×800 mm	1000×1000 mm	1000×1000 mm	1000×1000 mm
Working temperature	-10° - +40 °C				
Output signal	RS 232				
IP rating	IP 68 construction, IP 66/67 indicator				
Power supply	230V AC, 50Hz				
Display	LCD (backlit)				

Technical data:

	WPT/4 1500H8	WPT/4 3000H8	WPT/4 1500H9	WPT/4 3000H9	WPT/4 3000H10	WPT/4 6000H10
Max capacity	1500 kg	3000 kg	1500 kg	3000 kg	3000 kg	6000 kg
Readability	500 g	1000 g	500 g	1000 g	1000 g	2000 g
Tare range	-1500 kg	-3000 kg	-1500 kg	-3000 kg	-3000 kg	-6000 kg
Pan size	1200×1200 mm	1200×1200 mm	1500×1500 mm	1500×1500 mm	1500×2000 mm	1500×2000 mm
Working temperature	-10° - +40 °C					
Output signal	RS 232					
IP rating	IP 68 construction, IP 66/67 indicator					
Power supply	230V AC, 50Hz					
Display	LCD (backlit)					

Additional equipment:

RACK FOR HEAD	RAMPS FOR LOW PROFILED SCALE
LCD ADDITIONAL DISPLAY	COMPUTER SOFTWARE: PW-WIN, RAD-KEY, REC-FS, LS-FS
LARGE SIZE ADDITIONAL DISPLAY	RS 232/RS 485 CONVERTER
"KAFKA" THERMAL PRINTER	EXTERNAL POWER OUTPUT
NEEDLE PRINTER "EPSON"	