



Security Limited

<http://www.acesee.com>

Tel: 86-20-8202 9880 ext 816 Fax: 86-20-8202 94 78

E-mail/MSN: wendy@acesee.com Skype: wendy.acesee



Add: The 2nd Floor of Building C#, Yushu Industrial Zone, Science Park, Guangzhou, China 510660

EX-Works Price List for Distributors

-Version: 201112B

4CH H.264 Network DVR >>

PICTURE SHOW	MODEL NO.	UNIT PRICE USD/SET	SPECIFICATION
 <p>D1*4CH, Support Max 2TB</p> 	AS-0470	\$39.80	<ul style="list-style-type: none"> *Video I/O: 4CH (BNC 4CH In / 1CH Out, VGA 1CH Out) *VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz *Compression Method: H.264 *Display Resolution: PAL: 704*576, NTSC: 704*480 *Recording Frame Rate (IPS) & Resolution: NTSC: 120/704x480; 120/704x240; 120/352x240; PAL: 100/704x576; 100/704x288; 100/352x288 *1 SATA 3.5" Hard Disk Interface, Support Max 2TB *Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector *Backup: USB2.0 and Network *Support USB Mouse, Remote Controller *With CMS Software *PTZ Control: RS-485 *Multilingual support: 14 Type *Power Input : DC12V, 3A (Adapter Included) *Dimension: 274*214.5*45mm(L*D*H), Weight: 2.5Kg

 <p>D1*4CH, Support Max 2TB</p> 	AS-0460	\$48.80	<ul style="list-style-type: none"> *Video I/O: 4CH (BNC 4CH In / 1CH Out, VGA 1CH Out) *Audio I/O: RCA 4CH Input /1CH Output *Alarm I/O: 4CH Input / 1CH Output *VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz *Compression Method: H.264 *Display Resolution: PAL: 704*576, NTSC: 704*480 *Recording Frame Rate (IPS) & Resolution: NTSC: 120/704x480; 120/704x240; 120/352x240; PAL: 100/704x576; 100/704x288; 100/352x288 *1 SATA 3.5" Hard Disk Interface, Support Max 2TB *Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector *Backup: USB2.0 and Network *Support USB Mouse, Remote Controller, Panel Operating *PTZ Control: RS-485 *Multilingual support: 14 Type *Power Input : DC12V, 3A (Adapter Included) *Dimension: 354*230*45mm(L*D*H), Weight: 4Kg
---	---------	----------------	---



D1*4CH, Support Max 2TB

ACESEE

AS-0420

\$48.80

*Video I/O: 4CH (BNC 4CH In / 1CH Out, VGA 1CH Out)
 *Audio I/O: RCA 4CH Input /1CH Output
 *Alarm I/O: 4CH Input / 1CH Output
 *VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz
 *Compression Method: H.264
 *Display Resolution: PAL: 704*576, NTSC: 704*480
 *Recording Frame Rate (IPS) & Resolution:
 NTSC: 120/704x480; 120/704x240; 120/352x240;
 PAL: 100/704x576; 100/704x288; 100/352x288
 *1 SATA 3.5" Hard Disk Interface, Support Max 2TB
 *Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector
 *Backup: USB2.0 and Network
 *Support USB Mouse, Remote Controller, Panel Operating
 *PTZ Control: RS-485
 *Multilingual support: 14 Type
 *Power Input : DC12V, 3A (Adapter Included)
 *Dimension: 354(W)*230(D)*45(H)mm, Weight: 4.2 Kg

8CH H.264 Network DVR >>

PICTURE SHOW

MODEL NO.

UNIT PRICE
USD/SET

SPECIFICATION



D1*2CH, Support Max 2TB

ACESEE

AS-0860

\$63.80

*Video I/O: 8CH (BNC 8CH In / 1CH Out, VGA 1CH Out)
 *Audio I/O: RCA 8CH Input /1CH Output
 *Alarm I/O: 8CH Input / 1CH Output
 *VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz
 *Compression Method: H.264
 *Display Resolution: PAL: 704*576, NTSC: 704*480
 *Recording Frame Rate (IPS) & Resolution:
 NTSC: 60/704x480; 120/704x240; 120/352x240;
 PAL: 50/704x576; 100/704x288; 100/352x288
 *1 SATA 3.5" Hard Disk Interface, Support Max 2TB
 *Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector
 *Backup: USB2.0 and Network
 *Support USB Mouse, Remote Controller, Panel Operating
 *PTZ Control: RS-485
 *Multilingual support: 14 Type
 *Power Input : DC12V, 5A (Adapter Included)
 *Dimension: 354*230*45mm(L*D*H), Weight: 4Kg



D1*2CH, Support Max 2TB

ACESEE

AS-0820

\$63.80

- *Video I/O: 8CH (BNC 8CH In / 1CH Out, VGA 1CH Out)
- *Audio I/O: RCA 8CH In /1CH Out
- *Alarm I/O: 8CH Input / 1CH Output
- *VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz
- *Compression Method: H.264
- *Display Resolution: PAL: 704*576, NTSC: 704*480
- *Recording Frame Rate (IPS) & Resolution:
NTSC: 60/704x480; 120/704x240; 240/352x240;
PAL: 50/704x576; 100/704x288; 200/352x288
- *1 SATA 3.5" Hard Disk Interface, Support Max 2TB
- *Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector
- *Backup: USB2.0 and Network
- *Support USB Mouse, Remote Controller, Panel Operating
- *PTZ Control: RS-485
- *Multilingual support: 14 Type
- *Power Input : DC12V, 5A (Adapter Included)
- *Dimension: 354(W)×230(D)×45(H)mm, Weight: 4.2 Kg

16CH H.264 Network DVR >>

PICTURE SHOW

MODEL NO.

UNIT PRICE
USD/SET

SPECIFICATION



Support Max 2TB

ACESEE

AS-1660

\$78.00

- *Video I/O: 16CH (BNC 16CH In / 1CH Out, VGA 1CH Out)
- *Audio I/O: RCA 2CH Input /1CH Output
- *Alarm I/O: 16CH Input / 1CH Output
- *VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz
- *Compression Method: H.264
- *Display Resolution: PAL: 704*576, NTSC: 704*480
- *Recording Frame Rate (IPS) & Resolution:
NTSC: 480/352x240; PAL: 400/352x288
- *1 SATA 3.5" Hard Disk Interface, Support Max 2TB
- *Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector
- *Backup: USB2.0 and Network
- *Support USB Mouse, Remote Controller, Panel Operating
- *PTZ Control: RS-485
- *Multilingual support: 14 Type
- *Power Input : DC12V, 5A (Adapter Included)
- *Dimension: 354*230*45mm(L*D*H), Weight: 4.3Kg



Support Max 2TB

ACESEE

AS-1620

\$78.00

*Video I/O: 16CH (BNC 16CH In / 1CH Out, VGA 1CH Out)
*Audio I/O: RCA 2CH Input /1CH Output
*Alarm I/O: 16CH Input / 1CH Output
*VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz
*Compression Method: H.264
*Display Resolution: PAL: 704*576, NTSC: 704*480
*Recording Frame Rate (IPS) & Resolution:
NTSC: 480/352x240; PAL: 400/352x288
*1 SATA 3.5" Hard Disk Interface, Support Max 2TB
*Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector
*Backup: USB2.0 and Network
*Support USB Mouse, Remote Controller, Panel Operating
*PTZ Control: RS-485
*Multilingual support: 14 Type
*Power Input : DC12V, 5A (Adapter Included)
*Dimension: 354*230*45mm(L*D*H), Weight: 4.5Kg



D1*4CH, Support Max 2X2TB

HDMI Output, 2 SATA

ACESEE

AS-1630HC

\$139.00

*Video I/O: 16CH (BNC 16CH In / 1CH Out, **SPOT 1CH Out**,
VGA 1CH Out 1280*1024, **HDMI 1CH Out** 1920*1080P)
*Audio I/O: RCA 16CH Input /1CH Output
*Alarm I/O: 16CH Input / 1CH Output
*VGA Output: 800*600/60Hz, 1024*768/Hz, 1280*1024/Hz
*Compression Method: H.264
*Display Resolution: PAL: 704*576, NTSC: 704*480
*Recording Frame Rate (IPS) & Resolution:
NTSC: 120/704x480; 240/704x240; 480/352x240;
PAL: 100/704x576; 200/704x288; 400/352x288
***2 SATA** 3.5" Hard Disk Interface, Support Max **2X2TB**
*Network Port: 1 RJ-45, 10/100Mbps Ethernet Connector
*Backup: USB2.0 and Network
*Support USB Mouse, Remote Controller, Panel Operating
*PTZ Control: RS-485
*Power Input : DC12V, 5A (Adapter Included)
*Dimension: 430(W)x345(D)x66(H)mm, Weight: 7.2Kg

Terms & Conditions >>

1. Price Terms: EX-Works Guangzhou Factory
2. Terms of Payment: T/T, L/C, Paypal, Western Union
3. Warranty: 12 Months
4. MOQ: 10PCS Each Model After Sample Order