


H.264 DVR

4CH H.264 Stand-Alone Economic Network DVR







Features

- Adopts the standard Main profile H.264 compression technology,D1 and CIF can be adjusted supports 4ch recording, Network transmission, and playback simultaneously
- Support dual-stream transmission for all channels
- Support Multiplex operation: live, record, playback, backup, network transmission, mobile phone surveillance
- ◆ Support backup with USB Flash Disk, Movable hard discus writer, Network
- ◆ Support 1channel. Main output, 1channel VGA output
- Support password watermark function to avoid data modification
- Support Email alarm
- ◆ Mobile phone surveillance (Win CE/Symbain/iPhone/Blackberry)
- Support Multi-language OSD
- Support USB mouse

Specifications

| Model Name | EN-6704V |
|---------------------------|---|
| Operating System | Embedded Linux OS |
| Video Compression Format | Main Profile H.264 |
| Video Input | 4 Channels BNC |
| Video Output | 1 Channel BNC, 1 Channel VGA(1280*1024) |
| Display Picture | 1/4 |
| Multiplex Operation | Live\display\Playback\Recording\Backup\ |
| | Mobile phone Surveillance \Network simultaneously |
| Display Resolution | PAL:D1(704*576),NTSC:D1 (704*480) |
| Recording Mode | Manual\Timer\Motion Detection\Alarm |
| Recording Frame Rate | D1@50fps,HD1@100fps,CIF@100fps adjustable |
| Recording Resolution | PAL:D1(704*576),HD1(704*288),CIF(352*288), |
| | NTSC:D1(704*480),HD1(704*240),CIF(352*240) |
| Recording Playback | 1/4 channel playback simultaneously (Optional playback channel) |
| Recording Backup | USB、Moved Hard Disk、USB Writer、Network |
| Network Transmission | 4Channels real-time Network transmission with CIF resolution |
| Recording Play | Special player, Support AVI file format conversion |
| JPEG Capture function | Support,3M Pixels@10fps |
| Email Alarm | Send pieces to the designated email |
| PTZ | Supports (PELCO-D,PELCO-P) |
| HDD | Support 1 SATA HDD, capacity to 2T |
| Network and Protocol | 1 RJ-45 10/100M via Ethernet, Support TCP/IP、PPPOE、DHCP、DNS、 |
| | DDNS、NTP、UPNP |
| IE Browser | Support |
| Client Software | Support |
| Dual Stream | Support (Main and secondary interchange) |
| Group play | Max Support five users online access |
| Watermark | Support |
| Multi-language | Support |
| Mobile Phone Surveillance | Support Windows\ Symbian\ iPhone\Blackberry Operation System |
| Mouse Interface | USB2.0 |
| Backup interface | USB2.0 |
| DST | Support |
| Power | DC12V/3A |
| Working Temperature | 0°C-50°C |
| Working Humidity | 10%-90% |
| Dimension | 354(W)×230(D)×45(H) |

Design and specifications are subject to change without notice.